


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00129	Connector, dc plug, 5.5x2.5xL18.5 mm, molding style, spring contacts	2	
2	30-00338	Wire, 1C TS, 20 AWG, UL1185, 300V, 80C, 2.95 mm, shielded, VW-1, PVC	1	
3	24-00358	Overmold, dc 90° plug, 5.5 mm	2	PVC, black



**Notes:**  
Functionally equivalent components may be substituted  
Cable rated for 48 V, 7.0 A

Wiring Diagram		
50-00129	wire color	50-00129
center	white	center
sleeve	shield	sleeve

Revision:	Date:	Description:	Prepared:	Notes:	<h1>TENSILITY</h1> <p>tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com</p>
A	4/19/2021	Initial release	AW <small>Digitally signed by AW Date: 2021.04.19 15:20:38 -07'00'</small>		
			Verified:	Function test: no open, no short circuit, no intermittent	Size: Part number:
			JC <small>Digitally signed by JC Date: 2021.04.21 10:44:52 -07'00'</small>	Description:	A 10-03927
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Cable, 1830 mm, 5.5x2.5x9.5 mm 90° 50-00129 dc plug to same, 20 AWG, 30-00338 wire	Scale: 1:1
					Sheet 1 of 1

5

4

3

2

1