

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD		STORAGE TEMPERATURE RANGE		-10 °C TO 60 °C ⁽²⁾	
OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C ⁽¹⁾	OPERATING HUMIDITY RANGE	RELATIVE HUMIDITY	95 % RH MAX. ⁽³⁾	
VOLTAGE	50 V AC	STORAGE HUMIDITY RANGE	40 °C TO 70 °C ⁽²⁾		
CURRENT	0.3 A				
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	Q	T	AT
CONSTRUCTION		GENERAL EXAMINATION VISUALLY AND BY MEASURING INSTRUMENT. ACCORDING TO DRAWING.			
MARKING	CONFIRMED VISUALLY.		X	X	X
ELECTRIC CHARACTERISTICS					
CONTACT RESISTANCE	100 mA (DC OR 1000 HZ).	60 mΩ MAX.	X	-	-
INSULATION RESISTANCE	100 V DC	100 MΩ MIN.	X	-	-
VOLTAGE PROOF	150 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X	X	X
MECHANICAL CHARACTERISTICS					
INSERTION AND WITHDRAWAL FORCE	MEASURED BY APPLICABLE CONNECTOR.	INSERTION FORCE: 100.8 N MAX. WITHDRAWAL FORCE: 4.2 N MIN.	X	-	-
MECHANICAL OPERATION	50 TIMES INSERTIONS AND EXTRACTATIONS.	① CONTACT RESISTANCE: 70 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-	-
VIBRATION	FREQUENCY 10 TO 55 Hz. SINGLE AMPLITUDE: 0.75 mm, WITH 10 CYCLES IN 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-	-
SHOCK	490 ms ² , DURATION OF PULSE 11 ms 3 TIMES IN 3 DIRECTIONS.		X	-	-
ENVIRONMENTAL CHARACTERISTICS					
DAMP HEAT (STEADY STATE)	EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 h.	① CONTACT RESISTANCE: 70 mΩ MAX. ② INSULATION RESISTANCE: 100 MΩ MIN.	X	-	-
RAPID CHANGE OF TEMPERATURE	TEMPERATURE: -55 → +15 ~ +35 → +85 → +15 ~ +35 °C TIME 30 → 2 ~ 3 → 30 → 2 ~ 3 min. UNDER 5 CYCLES.	③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-	-
DRY HEAT	EXPOSED AT 85 °C, 96h.	① CONTACT RESISTANCE: 70 mΩ MAX.	X	-	-
COLD	EXPOSED AT -55 °C, 96h.	② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-	-
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.	NO HEAVY CORROSION.	X	-	-
SULPHUR DIOXIDE	EXPOSED IN 10 PPM FOR 96 h. (TEST STANDARD: JIS C 0090)	① CONTACT RESISTANCE: 70 mΩ MAX. ② NO HEAVY CORROSION.	X	-	-
RESISTANCE TO SOLDERING HEAT	1) REFLOW SOLDERING: 250 °C MAX, : 220 °C MIN, FOR 60 s 2) SOLDERING IRONS : 360 °C, FOR 5 s	NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINAL.	X	-	-
SOLDERABILITY	SOLDERED AT SOLDER TEMPERATURE: 240 °C, FOR IMMERSION DURATION, 3 sec.	A NEW UNIFORM COATING OF SOLDER SHALL OVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSERD.	X	-	-
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
△					
REMARK ⁽¹⁾ TEMPERATURE RISE INCLUDED WHEN ENERGIZED. ⁽²⁾ THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED. ⁽³⁾ NO DEW CONDENSATION IS PERMITTED.					
Unless otherwise specified, refer to JIS C 5402.					
Note QT: Qualification Test AT: Assurance Test X: Applicable Test		DRAWING NO.	ELC4-151955-25		
HRS		SPECIFICATION SHEET		PART NO. FX10A-168P-SV (71)	
		HIROSE ELECTRIC CO., LTD.		CODE NO. GL570-0044-8-71	
				DRAWN AK: SUZUKAWA 06.02.03	
		APPROVED	HS. OKAWA	06.02.06	
		CHECKED	HS. OZAWA	06.02.06	
		DESIGNED	K.Y. NAKAMURA	06.02.06	
		DRAWN	AK: SUZUKAWA	06.02.03	
				1/1	