



Ex protective-earth terminal ATEX-certified Tension-spring connection, Mounting type: Mounting rail TS 15/5.5, Rated cross-section: 2.5 mm<sup>2</sup>, Width: 5.1 mm, Colour: Green-yellow

### Business data

|  |  |
|--|--|
| Article number                             | 1709.2   |
| Article name                               | ZSLN 2,5/2A/15 Ex GNYE                         |
| GTIN (EAN)                                 | 4044211059385                                  |
| Explosion-proof version (EEx e)            | yes  |
| Packaging unit                             | 100  |
| Quantity unit                              | PC   |
| Weight per piece (not including packaging) | 6.6 g  |
| Weight per piece (including packaging)     | 7 g  |
| Unit of weight                             | G  |
| Customs number                             | 85369010                                       |
| Country of origin                          | DE   |
| Product description                        | Ex protective earthing terminal ATEX-certified |
| Colour                                     | Green-yellow                                   |

### Technical data

#### Dimensions

|                  |        |
|------------------|--------|
| Length           | 40 mm  |
| Width            | 5.1 mm |
| Height TS 15/5.5 | 34 mm  |

#### Ratings

|                      |                     |
|----------------------|---------------------|
| Rated cross-section  | 2.5 mm <sup>2</sup> |
| Overvoltage category | III                 |
| Contamination degree | 3                   |

#### Connection data

|  |                           |
|--|---------------------------|
| Connection principle                                     | Tension-spring connection |
| Connection position                                      | Diagonal                  |
| Connections  | 2                         |
| Number of terminals per level                            | 2                         |
| Number of levels   | 1                         |
| Wire cross-section single-core (rigid) / stranded, min.  | 0.5 mm <sup>2</sup>       |
| Wire cross-section single core (rigid)/stranded, max.    | 4 mm <sup>2</sup>         |
| Wire cross-section stranded, min.                        | 0.5 mm <sup>2</sup>       |
| Wire cross-section stranded, max.                        | 4 mm <sup>2</sup>         |
| Wire cross-section stranded with wire-end ferrules, min. | 0.5 mm <sup>2</sup>       |
| Wire cross-section stranded with wire-end ferrules, max. | 2.5 mm <sup>2</sup>       |
| Wire cross-section AWG, min.                             | 20                        |
| Wire cross-section AWG, max.                             | 12                        |
| Stripping length   | 10 mm                     |

#### Materials

|                           |               |
|---------------------------|---------------|
| Insulation housing        | Polyamide 6.6 |
| Flammability class UL 94  | V-0           |
| Working temperature, min. | -40 °C        |
| Working temperature, max. | 120 °C        |

---

### Technical data

---

#### Further technical data

|                                     |       |
|-------------------------------------|-------|
| Mounting type                       | TS 15 |
| Gauge plug acc. to EN 60 947-1      | A3    |
| Number of cross-connection channels | 1     |
| End plate required                  | ✓     |
| Number of test pick-off options     | 2     |

#### Environmental Product Compliance

|                                |            |
|--------------------------------|------------|
| REACH Conform                  | yes        |
| REACH Reference date           | 2023-01-17 |
| REACH Candidate Substance Note | No         |
| RoHS Conform                   | yes        |

### Approvals

#### Standards and regulations

|                           |                 |
|---------------------------|-----------------|
| ATEX certification number | TÜV ATEX 7093 U |
| EAC approval              | TR ZU 004/2011  |
| EAC approval granted      | yes             |

#### CSA approval

|                                  |              |
|----------------------------------|--------------|
| CSA approval                     | C22.2 No 158 |
| CSA approval granted             | yes          |
| CSA wire cross-section AWG, min. | 20           |
| CSA wire cross-section AWG, max. | 12           |
| CSA stripping length             | 10 mm        |

#### CSAus approval

|                                    |         |
|------------------------------------|---------|
| CSAus approval                     | UL 1059 |
| CSAus approval granted             | yes     |
| CSAus wire cross-section AWG, min. | 20      |
| CSAus wire cross-section AWG, max. | 12      |
| CSAus stripping length             | 10 mm   |

#### cUL Recognized

|  |              |
|--|--------------|
| cUL approval   | C22.2 No 158 |
| cUL wire cross-section single-core (rigid) AWG, min. | 20           |
| cUL wire cross-section single-core (rigid) AWG, max. | 12           |
| cUL wire cross-section stranded AWG, min.            | 20           |
| cUL wire cross-section stranded AWG, max.            | 12           |
| cUL wire material                                    | Cu           |
| cUL Recognized                                       | 1            |

#### KEMA KEUR approval

|   |                     |
|---|---------------------|
| KEMA KEUR approval                                | EN 60947-7-2:2009   |
| KEMA KEUR approval granted                        | yes                 |
| KEMA wire cross-section single core (rigid), min. | 0.5 mm <sup>2</sup> |
| KEMA wire cross-section single-core (rigid), max. | 4 mm <sup>2</sup>   |
| KEMA wire cross-section stranded, min.            | 0.5 mm <sup>2</sup> |
| KEMA wire cross-section stranded, max.            | 4 mm <sup>2</sup>   |

### Approvals


#### UL Recognized

|   |         |
|---|---------|
| UL approval   | UL 1059 |
| UL wire cross-section single-core (rigid) AWG, min. | 20      |
| UL wire cross-section single-core (rigid) AWG, max. | 12      |
| UL wire cross-section stranded AWG, min.            | 20      |
| UL wire cross-section stranded AWG, max.            | 12      |
| UL wire material                                    | Cu      |
| UL factory wiring                                   | 1       |
| UL field wiring                                     | 1       |
| UL Recognized                                       | 1       |

#### DNV GL Approval

|   |   |
|---|---|
| DNV GL Certificate number                           | TAE00000Y7                                |
| DNV GL Location Classes                             | Temperature: B, Humidity: B, Vibration: A |
| DNV GL approval granted                             | 1   |
| DNV GL rated cross-section                          | 2.5 mm <sup>2</sup>                       |
| DNV GL rated voltage                                | 800 V                                     |
| DNV GL test standard                                | IEC 60947-7-2:2009                        |
| DNV GL wire cross-section single-core (rigid), max. | 4 mm <sup>2</sup>                         |
| DNV GL wire cross-section stranded, max.            | 2.5 mm <sup>2</sup>                       |

### Media



### Accessories

#### End plate



End plate, Width: 1.5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN)    | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>3757.2</u>  | ZAP SR BG    | 4044211060701 | 50             |

#### Actuating tool



Actuating tool, No. of poles: 1, Colour: Black

| Article number | Article name          | GTIN (EAN)    | Packaging unit |
|----------------|-----------------------|---------------|----------------|
| <u>3808.0</u>  | BWMA 1 (0,5 x 3,5 mm) | 4044211078850 | 1 ST           |

#### End stop



End stop, Mounting type: Mounting rail TS 15/5.5, Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN)    | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>3812.2</u>  | ZES 15 BG    | 4044211080617 | 50 ST          |

#### Test adapter



Test adapter, Pitch size: 5.1 mm, Colour: Beige

| Article number | Article name | GTIN (EAN)    | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>3740.2</u>  | ZTA 2,5 BG   | 4044211060497 | 10 ST          |

## 1709.2 ZSLN 2,5/2A/15 Ex GNYE

### Quick marking



Terminal marker / Pocket Maxicard, Length: 5 mm, Width: 5 mm, Colour: White

| Article number | Article name   | GTIN (EAN)    | Packaging unit |
|----------------|----------------|---------------|----------------|
| <u>4600.7</u>  | PMC SB 5/50 WH | 4044211088903 | 500 ST         |

### Four-way cover



Cover, Length: 6.7 mm, Width: 20.4 mm, Colour: Yellow

| Article number | Article name   | GTIN (EAN)    | Packaging unit |
|----------------|----------------|---------------|----------------|
| <u>3706.0</u>  | ZAD 2,5/4/B YE | 4044211060244 | 20 ST          |

### Reducing sleeves



Reducing sleeve, Width: 51 mm, Pitch size: 5.1 mm, Colour: Grey

| Article number | Article name        | GTIN (EAN)    | Packaging unit |
|----------------|---------------------|---------------|----------------|
| <u>3751.6</u>  | ZRH 2,5/0,25-0,5 GR | 4044211060602 | 1000 ST        |



Reducing sleeve, Width: 51 mm, Pitch size: 5.1 mm, Colour: White

| Article number | Article name        | GTIN (EAN)    | Packaging unit |
|----------------|---------------------|---------------|----------------|
| <u>3750.7</u>  | ZRH 2,5/0,13-0,2 WH | 4044211060596 | 1000 ST        |



Reducing sleeve, Width: 51 mm, Pitch size: 5.1 mm, Colour: Black

| Article number | Article name        | GTIN (EAN)    | Packaging unit |
|----------------|---------------------|---------------|----------------|
| <u>3752.4</u>  | ZRH 2,5/0,75-1,0 BK | 4044211060619 | 1000 ST        |