

In case of consideration for using Autom otive equipm ent/device which dem and high re liability, kindly contactour sales w indow correspondents.

APPLICABLE STANDARD		STORAGE TEMPERATURE RANGE		-10 °C TO 60 °C (2)	
OPERATING TEMPERATURE RANGE		-55 °C TO 85 °C (1)		OPERATING HUMIDITY RANGE	
RATING VOLTAGE		100 V AC		40 % TO 80 %	
CURRENT		0.5 A		STORAGE HUMIDITY RANGE	
				40 % TO 70 % (2)	
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	Q/T	A/T	
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X	
MARKING	CONFIRMED VISUALLY.		X	X	
ELECTRIC CHARACTERISTICS					
CONTACT RESISTANCE	100 mA (DC OR 1000 Hz).	40 mΩ MAX.	X	-	
CONTACT RESISTANCE	20 mV MAX, 1 mA(DC OR 1000Hz)	50 mΩ MAX.	X	-	
MILLIVOLT LEVEL METHOD					
INSULATION RESISTANCE	250 V DC	100 MΩ MIN.	X	-	
VOLTAGE PROOF	300 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X	-	
MECHANICAL CHARACTERISTICS					
MECHANICAL OPERATION	100 TIMES INSERTIONS AND EXTRACTIONS.	① CONTACT RESISTANCE: 50 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-	
VIBRATION	FREQUENCY 10 TO 55 Hz, AMPLITUDE : 1.5 mm, AT 2h FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-	
SHOCK	490 m/s ² , DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.		X	-	
ENVIRONMENTAL CHARACTERISTICS					
DAMP HEAT (STEADY STATE)	EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 hrs.	① CONTACT RESISTANCE: 50 mΩ MAX. ② INSULATION RESISTANCE: 100 MΩ MIN.	X	-	
RAPID CHANGE OF TEMPERATURE	TEMPERATURE: -55 → +15 ~ +35 → +85 → +15 ~ +35 °C TIME 30 → MAX 5 → 30 → MAX 5 min UNDER 5 CYCLES.	③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-	
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.	① CONTACT RESISTANCE: 50 mΩ MAX. ② NO HEAVY CORROSION.	X	-	
HYDROGEN SULPHIDE	EXPOSED IN 3 PPM FOR 96 h. (TEST STANDARD: JEIDA 38)		X	-	
RESISTANCE TO SOLDERING HEAT	1) REFLOW SOLDERING : 250 °C MAX, : 220 °C MIN, FOR 60 s 2) SOLDERING IRONS : 360 °C, FOR 5 s	NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.	X	-	
SOLDERABILITY	SOLDERED AT SOLDER TEMPERATURE: 240 ± 3 °C, FOR IMMERSION DURATION, 3 s.	A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSERD.	X	-	
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
△			APPROVED	HS. OKAWA 06.04.21	
			CHECKED	HS. OZAWA 06.04.21	
			DESIGNED	TK. YANAGISAWA 06.04.20	
			DRAWN	TK. YANAGISAWA 06.04.20	
REMARK ① TEMPERATURE RISE INCLUDED WHEN ENERGIZED. ② THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED.					
Unless otherwise specified, refer to MIL-STD-1344.					
Note Q: Qualification Test A: Assurance Test X: Applicable Test		DRAWING NO.	ELC4-084971-23		
HRS		SPECIFICATION SHEET		PART NO. FX6-80P-0.8SV (93)	
HIROSE ELECTRIC CO., LTD.		CODE NO.	CL576-0007-0-93		△ 1/1