

HDC enclosures HDC IP68 24B TSS 1PG36

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



The new RockStar® enclosures are resistant to seawater and offer a high degree of shock resistance, meet IP 68 and IP 69K, and have been developed for use under extreme environmental conditions and designed for the high vibration requirements acc. to DIN EN 61373 cat. 2 (bogie). As such, this housing family is ideally suited for fault- and maintenance-free operation of heavy-duty connectors in transport and traffic engineering as well as in power engineering and in applications with extreme requirements. During development, measures were also implemented to make the enclosures extremely EMC-resistant.

General ordering data

Order No.	1083010000
Type	HDC IP68 24B TSS 1PG36
Version	HDC enclosures, Size: 8, Protection degree: IP 68, Plug housing, Screw plug, Standard, Size of cable entries: PG 36
GTIN (EAN)	4032248846474
Qty.	1 pc(s).

**HDC enclosures
HDC IP68 24B TSS 1PG36**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Dimensions and weights

Length	191 mm	Width	58 mm
Height	110.5 mm	Net weight	660 g

Temperatures

Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	125 °C
----------------------------------	--------	----------------------------------	--------

Dimensions

Total length housing	191 mm	Width housing C	58 mm
Height of housing B	110.5 mm	Cable entry	w. threading

General data

Housing main material	diecast aluminium
-----------------------	-------------------

Version

Design of housing	Plug housing	Size	8
Design	Standard	Top part/bottom part/lid	upper part
Design of locking system	Screw plug	Cable entry	w. threading
Size of cable entries	PG 36	Number of cable entry on top	0
Number of cable entry sideways	1		

Classifications

ETIM 2.0	EC000437	ETIM 3.0	EC000437
UNSPSC	30-21-18-01	eClass 4.1	27-14-08-05
eClass 5.1	27-14-34-19	eClass 6.2	27-14-34-19
eClass 7.1	27-44-05-15		

Approvals

Approvals



ROHS	Conform
------	---------

Data sheet...

**HDC enclosures
HDC IP68 24B TSS 1PG36**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

