

B45190E, Tantalum, MnO2 Tantalum, 33 uF, 20%, 4 V, SMD, Molded, Low Profile, 3528, Height Max = 1.2mm



| General Information | |
|---------------------|--|
| Supplier: | KEMET |
| Series: | B45190E |
| Dielectric: | MnO2 Tantalum |
| Style: | SMD Chip |
| Description: | SMD, Molded, Low Profile |
| Features: | Low Profile |
| RoHS: | Yes |
| Termination: | Tin |
| Notes: | Obsolete. Old Part Number [Obsolete] Was B45190E0336M206 |

| Dimensions | |
|------------|----------------|
| Footprint | 3528 |
| L | 3.5mm +/-0.2mm |
| W | 2.8mm +/-0.2mm |
| H | 1.2mm MAX |
| S | 0.8mm +/-0.3mm |
| F | 2.2mm +/-0.1mm |
| K | 1mm TYP |

| Specifications | |
|------------------------|------------------------------|
| Capacitance: | 33 uF |
| Capacitance Tolerance: | 20% |
| Voltage DC: | 4 VDC (85C), 2.68 VDC (125C) |
| Temperature Range: | -55/+125C |
| Rated Temperature: | 85C |
| Dissipation Factor: | 8% |
| Failure Rate: | N/A |
| Leakage Current: | 1.3 uA |

| Packaging Specifications | |
|--------------------------|------------|
| Packaging: | T&R, 330mm |
| Packaging Quantity: | 10000 |