NTPS-24-1.3 Power Supply

N-Tron Networking Series

DIN Rail Mount Power Supply

The NTPS-24-1.3 is a DIN rail mount power supply designed to be used with N-Tron's Industrial Ethernet products.

INPUT SPECIFICATIONS:

AC Voltage	100-240VAC
Frequency	47 to 63Hz
Input Current	<0.6A @ AC 100Vin
_	<0.35A @ AC 196Vin
Inrush Current	36A max. @240VAC
DC Voltage	85-375VDČ

OUTPUT SPECIFICATIONS:

Output Voltage Maximum Load Ripple & Noise Voltage Accuracy 24-28VDC 1.3A <50mVpp ± 2%

ENVIRONMENTAL CHARACTERISTICS:

Full Nominal Load Storage Temperature Cooling -10°C - 60°C -25°C - 85°C Natural Convection

MECHANICAL CHARACTERISTICS:

Dimensions

Weight

45w x 75h x 91d (mm) 1.8" x 3.0" x 3.6" 230g (0.5 Pounds)

REGULATORY APPROVALS:


Hazardous Locations:

UL 1604 Listed, Class I Division 2 Hazardous Location Groups A, B, C, D



Safety:

CE ,EN 60950, EN 60204-1, EN 50178, IEC60950, UL 60950, UL 508 CAN/CSA-C22.2 No. 60950 (CUR) CAN/CSA-C22.2 No. 14 (CUL) EN 61000-6-3 and -4 (Emissions) (EN 55011, EN 55022, Class B) EN 61000-6-2 and EN 61000-6-1 (Immunity) VDE 0160/W2 (Transient protect)





www.redlion.net

Connect. Monitor. Control.

Americas sales@redlion.net

Asia-Pacific asia@redlion.net

Europe Middle East Africa

europe@redlion.net

+1 (717) 767-6511

As the global experts in communication, monitoring and control for industrial automation and networking, Red Lion has been delivering innovative solutions for over forty years. Our award-winning technology enables companies worldwide to gain real-time data visibility that drives productivity. Product brands include Red Lion, N-Tron and Sixnet. With headquarters in York, Pennsylvania, the company has offices across the Americas, Asia-Pacific and Europe. For more information, please visit www.redlion.net. Red Lion is a Spectris company.

