

20 19 18 17 16 15 14 13 12 11 9 8 7 6 5 4 3 2 1

VIEW ON MATING SIDE

⊙	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
⊙	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A

32 31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1

A = 16 STANDARD CONTACTS L = 3  
 C = 16 STANDARD CONTACTS L = 3  
 S = 32 TOTAL NUMBER OF CONTACTS

MARKING	STANDARD
PERFORMANCE LEVEL	G1/O = CONTACT AREA LEVEL I / TERMINATION TIN
FLUX PROOF	NO
FIXING CLIP	NO
DIMENSIONS	SD-85003-0001 SHT 1

C	G1/O	c2,4,6....32
A	G1/O	a2,4,6....32
CONTACT SYMBOL	PERFORMANCE LEVEL	CONTACT POSITION NUMBER

EC NO.1 2004-XXXX DRAWN N.S. 09/09/03 CHK'd G.L. 09/09/03 APPR. G.L. 09/09/03	QUALITY SYMBOLS	GENERAL TOLERANCES: (UNLESS SPECIFIED)	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION	DIMENSIONS:	SHT	REV		
	MAJOR	$\pm$	mm	$\pm$	mm	$\pm$	INCH	mm		
	CRITICAL	$\pm$	mm	$\pm$	mm	$\pm$	INCH	mm		
REV	DESCRIPTION	4 PLACES $\pm 0.1$	3 PLACES $\pm 0.1$	2 PLACES $\pm 0.1$	1 PLACE $\pm 0.1$	ANGULAR $\pm$	CAD FILENAME	MATERIAL NO.	DRAWING NO.	SHEET NO.
C		DRAWN BY & DATE S.S. 10/09/1999	CHECKED BY & DATE G.L. 10/09/1999	APPROVED BY & DATE G.L. 10/09/1999	TITLE: 96 POS MALE CONNECTOR ACCORDING DIN 41612 STYLE C CONTACTS ARRANGEMENT	D-85003-0634.S01	85003-0634	SD-85003-0634	1 OF 1	
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.						

24-border.DGN REV 4 96/06/12 LEVEL 6 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1