

Aug.1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All rights reserved. In case of consideration for using Automative equipment/device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD		-25 °C TO +85 °C		STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C	
RATING	OPERATING TEMPERATURE RANGE					
	VOLTAGE	AC 30 V , DC 42 V				
	CURRENT	2 A ⁽⁴⁾		APPLICABLE CABLE		
SPECIFICATIONS						
ITEM	TEST METHOD	REQUIREMENTS			QT	AT
CONSTRUCTION						
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.			X	X
MARKING	CONFIRMED VISUALLY.				X	X
ELECTRIC CHARACTERISTICS						
CONTACT RESISTANCE	CONTACT SHALL BE MEASURED AT DC 1 A	15 mΩ MAX.			X	X
	CONTACT SHALL BE MEASURED AT DC — A	— mΩ MAX.			—	—
INSULATION RESISTANCE	100 V DC.	1000 MΩ MIN.			X	X
VOLTAGE PROOF	300 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.			X	X
MECHANICAL CHARACTERISTICS						
CONTACT INSERTION AND WITHDRAWAL FORCES	— BY STEEL GAUGE.	INSERTION AND WITHDRAWAL FORCES : — N MIN.			—	—
CONNECTOR INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR LOCKING DEVICE WITH LOCK.	INSERTION AND WITHDRAWAL FORCES : 50 N MAX.			X	—
MECHANICAL OPERATION	1000 TIMES INSERTIONS AND EXTRACTATIONS.	CONTACT RESISTANCE: 30 mΩ MAX.			X	—
		— RESISTANCE: — mΩ MAX.			—	—
VIBRATION	FREQUENCY 10 TO 55 Hz, (1CYC, 5MIN) SINGLE AMPLITUDE 0.75 mm, AT 10CYC, FOR 3 DIRECTIONS	① NO ELECTRICAL DISCONTINUITY OF 10 μs. ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.			X	—
SHOCK	IN OPPOSITE DIRECTIONS OF EACH 3 DEMENSION ALAXIS FOR 3 TIMES AT 490 m/s ² DURATIONS OF PULSE 11 ms.	① NO ELECTRICAL DISCONTINUITY OF 10 μs. ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.			X	—
CONTACT RETENTION FORCE	APPLYING A PULL FORCE THE WIRE AFTER THE APPLICABLE CRIMPED CONTACT IS ASSEMBLED THE BODY	20 N MIN			X	—
BREAKING STRENGTH	MAX 30N SHALL BE APPLIED TO CABLE IN UP AND DOWN, LEFT AND RIGHT DIRECTIONS WHEN MATED	NO BREAKAGE OF CONNECTOR.			X	—
ENVIRONMENTAL CHARACTERISTICS						
DAMP HEAT (STEADY STATE)	EXPOSED AT 40°C, 90 TO 95 %, 96 h.	① INSULATION RESISTANCE: 10 MΩ MIN (AT HIGH HUMIDITY). ② INSULATION RESISTANCE: 100 MΩ MIN (AT DRY). ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			X	—
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55°C → R/T ⁽¹⁾ → +85°C → R/T TIME 30 → 10 TO 15 → 30 → 10 TO 15 min UNDER 5 CYCLES.	① INSULATION RESISTANCE: 100 MΩ MIN. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			X	—
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.	NO HEAVY CORROSION.			X	—
DRY HEAT	EXPOSED AT + 85 °C , 96 h.	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			X	—
COLD	EXPOSED AT - 55 °C , 96 h.	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			X	—
SEALING ⁽³⁾	EXPOSED AT A DEPTH OF 1m FOR 0.5 h.	NO WATER PENETRATION INSIDE CONNECTOR.			X	—
AIRTIGHTNESS ⁽³⁾	APPLY AIR PRESSURE 17.6 kPa FOR 0.5min TO INSIDE CONNECTOR	NO AIR BUBBLES INSIDE CONNECTOR			X	—
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
①						
REMARK				APPROVED	HY. KOBAYASHI	18.03.16
NOTES(1) R/T : ROOM TEMPERATURE				CHECKED	HY. KOBAYASHI	18.03.16
(2) ABOVE SPECIFICATIONS SHOWS THE VELVE IN ASSEMBLED CONDITION WITH APPLICABLE CRIMP CONTACT.				DESIGNED	DS. MATSUNE	18.03.16
(3) SEALING AND AIRTIGHTNESS SHALL BE TESTED BY APPLCIABLE CONNECTOR.				DRAWN	DS. MATSUNE	18.03.16
(4) 2 A RATE CURRENT IS THE MAXIMUM CURRENT FLOW PER CONTACT. THE CURRENT CAPACITY OF WHOLE CONNECTOR IS 17 A MAX.						
Unless otherwise specified, refer to IEC 60512.(JIS C 5402)						
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.	ELC-112154-31-00		
HRS	SPECIFICATION SHEET		PART NO.	HR30-7R-10PC(31)		
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL130-1012-5-31		1/1