

## Key **Features**

SuperClear® IPS panel technology | Frameless design | Versatile connectivity | Full HD 1080p resolution | Superior color rendering and intuitive settings



## Product **Description**

The ViewSonic® VA2259-smh is a 22" (21.5" viewable) Full HD LED monitor designed for both office and home use. With SuperClear® IPS Panel technology, this monitor offers best-in-class screen performance with ultra-wide viewing angles. Vivid 1920x1080 resolution and dual speakers, combined with a sleek edge-to-edge frameless design, deliver an immersive viewing experience for home entertainment and multimedia applications. What's more, the minimalistic design of this monitor makes it perfect for nearly seamless multi-screen setups. HDMI and VGA inputs deliver flexible connectivity options for both computing and gaming environments, while ViewSonic's exclusive ViewMode feature provides intuitive presets for optimized screen performance in different applications. In addition, Flicker-Free technology and a Blue Light Filter help to minimize eyestrain from extended viewing periods. With ViewSonic's industry-leading 3-year limited warranty, this monitor is a solid long-term investment for enterprise and home applications.



22" **DISPLAY** 



IPS **Panel** 



1920 x 1080 **RESOLUTION** 

Display Size (in.):   22	· Sync,
Panel Type:         IPS         Frequency Horizontal:         24~82kHz           Resolution:         1920 x 1080         Frequency Vertical:         50~75Hz           Static Contrast Ratio:         1000:1         Video Input:           Dynamic Contrast Ratio:         50,000,000:1         Analog Sync:         Separate Sync, Composite Sync on Green, TMDS           Light Source:         LED         Ergonomics:           Brightness:         250 cd/m2         Tilt (Forward/Back):         5° / 22°           Colors:         16.7M         Weight (imperial):         6.3           Response Time (Typical GTG):         14ms         Net (lbs):         6.3           Response Time (GTG w/OD):         5ms         Net Without Stand (lbs):         5.5           Viewing Angles:         178° horizontal, 178° vertical         Gross (lbs):         9.5           Backlight Life (Hours):         30,000         Weight (metric):         Net (kg):         2.8           Backlight Life (Hours):         Anti-glare, hard-coating (3H)         Net (kg):         2.8           Compatibility:         PC Resolution (max):         Up to 1920x1080 non-interlaced         Gross (kg):         4.3           Mac* Resolution (max):         Up to 1920x1080 non-interlaced         Packaging (in.):         22.1 x 17.4 x 6.1 </td <td>· Sync,</td>	· Sync,
Resolution: 1920 x 1080 Frequency Vertical: 50~75Hz  Static Contrast Ratio: 1000:1  Dynamic Contrast Ratio: 50,000,000:1  Light Source: LED  Brightness: 250 cd/m2 Tilt (Forward/Back): 5°/22°  Colors: 16.7M Weight (imperial):  Response Time (Typical GTG): 14ms Net (lbs): 6.3  Response Time (GTG w/OD): 5ms Net Without Stand (lbs): 5.5  Viewing Angles: 178° horizontal, 178° vertical Gross (lbs): 9.5  Backlight Life (Hours): 30,000 Weight (metric):  Panel Surface: Anti-glare, hard-coating (3H)  Mac* Resolution (max): Up to 1920x1080 non-interlaced Gross (kg): 4.3  Mac* Resolution (max): Up to 1920x1080 Dimensions (imperial) (WxHxD):  Connector: Packaging (in.): 22.1 x 17.4 x 6.1  Physical (in.): 19.7 x 14.8 x 7.9  Physical Without Stand (in.): 19.7 x 11.9 x 1.8  Dimensions (metric) (WxHxD):  Physical Without Stand (in.): 19.7 x 11.9 x 1.8  Dimensions (metric) (WxHxD):  Physical Without Stand (in.): 19.7 x 11.9 x 1.8  Dimensions (metric) (WxHxD):  Physical Without Stand (in.): 562 x 443 x 155	· Sync,
Static Contrast Ratio: 1000:1 Video Input:  Dynamic Contrast Ratio: 50,000,000:1 Analog Sync: Separate Sync, Composite Sync on Green, TMDS Sync on Green, TMDS  Light Source: LED Ergonomics:  Brightness: 250 cd/m2 Tilt (Forward/Back): 5° / 22°  Colors: 16,7M Weight (imperial):  Response Time (Typical GTG): 14ms Net (lbs): 6.3  Response Time (GTG w/OD): 5ms Net Without Stand (lbs): 5.5  Viewing Angles: 178° horizontal, 178° vertical Gross (lbs): 9.5  Backlight Life (Hours): 30,000 Weight (metric):  Panel Surface: Anti-glare, hard-coating (3H) Net Without Stand (kg): 2.8  Compatibility: Net Without Stand (kg): 2.5  PC Resolution (max): Up to 1920x1080 non-interlaced Gross (kg): 4.3  Mac* Resolution (max): Up to 1920x1080 Dimensions (imperial) (WxHxD):  Connector: Packaging (in.): 22.1 x 17.4 x 6.1  Physical Without Stand (in.): 19.7 x 11.9 x 1.8  Audio: Internal Speakers: 2-watt (x2)  Power:	Sync,
Dynamic Contrast Ratio: 50,000,000:1  Light Source: LED  Brightness: 250 cd/m2  Colors: 16.7M  Response Time (Typical GTG): 14ms  Response Time (GTG w/OD): 5ms  Net (lbs): 6.3  Response Time (GTG w/OD): 5ms  Net Without Stand (lbs): 5.5  Viewing Angles: 178° horizontal, 178° vertical  Backlight Life (Hours): 30,000  Panel Surface: Anti-glare, hard-coating (3H)  Compatibility: PC Resolution (max): Up to 1920x1080 non-interlaced  Mac* Resolution (max): Up to 1920x1080  Connector: Packaging (in.): 22.1 x 17.4 x 6.1  Physical (in.): 19.7 x 14.8 x 7.9  Physical Without Stand (in.): 19.7 x 11.9 x 1.8  Dimensions (metric) (WxHxD): Physical Without Stand (in.): 19.7 x 11.9 x 1.8  Dimensions (metric) (WxHxD): Physical Without Stand (in.): 19.7 x 11.9 x 1.8  Dimensions (metric) (WxHxD): 19.7 x 11.9 x 1.8	e Sync,
Light Source:  Brightness:  250 cd/m2  Tilt (Forward/Back):  50 / 220  Colors:  16.7M  Weight (imperial):  Response Time (Typical GTG):  Net (lbs):  Response Time (GTG w/OD):  5ms  Net Without Stand (lbs):  5.5  Viewing Angles:  1780 horizontal, 1780 vertical  Backlight Life (Hours):  30,000  Weight (metric):  Net (kg):  2.8  Compatibility:  PC Resolution (max):  Up to 1920x1080 non-interlaced  Mac* Resolution (max):  Up to 1920x1080  Dimensions (imperial) (WxHxD):  Physical Without Stand (in.):  Dimensions (metric) (WxHxD):  Physical Without Stand (in.):  Physical Without Stand (in	s Sync,
Brightness: 250 cd/m2 Tilt (Forward/Back): 5° / 22°  Colors: 16.7M Weight (imperial):  Response Time (Typical GTG): 14ms Net (lbs): 6.3  Response Time (GTG w/OD): 5ms Net Without Stand (lbs): 5.5  Viewing Angles: 178° horizontal, 178° vertical Gross (lbs): 9.5  Backlight Life (Hours): 30,000 Weight (metric):  Panel Surface: Anti-glare, hard-coating (3H) Net (kg): 2.8  Compatibility: Net Without Stand (kg): 2.5  PC Resolution (max): Up to 1920x1080 non-interlaced Gross (kg): 4.3  Mac* Resolution (max): Up to 1920x1080  Mac* Resolution (max): Up to 1920x1080  Connector: Packaging (in.): 22.1 x 17.4 x 6.1  3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1), Power in(3-pin plug (CEE22))  Audio: Physical Without Stand (in.): 19.7 x 11.9 x 1.8  Dimensions (metric) (WxHxD): Physical Without Stand (in.): 19.7 x 11.9 x 1.8  Dimensions (metric) (WxHxD): Packaging (mm): 562 x 443 x 155	
Colors: 16.7M Weight (imperial):  Response Time (Typical GTG): 14ms Net (lbs): 6.3  Response Time (GTG w/OD): 5ms Net Without Stand (lbs): 5.5  Viewing Angles: 178° horizontal, 178° vertical Gross (lbs): 9.5  Backlight Life (Hours): 30,000 Weight (metric):  Panel Surface: Anti-glare, hard-coating (3H) Net (kg): 2.8  Compatibility: Net Without Stand (kg): 2.5  PC Resolution (max): Up to 1920x1080 non-interlaced Gross (kg): 4.3  Mac* Resolution (max): Up to 1920x1080 Dimensions (imperial) (WxHxD):  Connector: Packaging (in.): 22.1 x 17.4 x 6.1  3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1), Power in(3-pin plug (CEE22))  Audio: Dimensions (metric) (WxHxD):  Power: Dimensions (metric) (WxHxD):  Packaging (mm): 562 x 443 x 155	
Response Time (Typical GTG): 14ms  Net (lbs): 6.3  Response Time (GTG w/OD): 5ms  Net Without Stand (lbs): 5.5  Viewing Angles: 178° horizontal, 178° vertical Gross (lbs): 9.5  Backlight Life (Hours): 30,000  Panel Surface: Anti-glare, hard-coating (3H)  Compatibility: Net (kg): 2.8  Compatibility: Net Without Stand (kg): 2.5  PC Resolution (max): Up to 1920x1080 non-interlaced Gross (kg): 4.3  Mac° Resolution (max): Up to 1920x1080  Dimensions (imperial) (WxHxD):  Connector: Packaging (in.): 22.1 x 17.4 x 6.1  3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1), Power in(3-pin plug (CEE22))  Audio: Dimensions (metric) (WxHxD):  Physical Without Stand (in.): 19.7 x 14.8 x 7.9  Physical Without Stand (in.): 562 x 443 x 155  Power:	
Response Time (GTG w/OD): 5ms  Viewing Angles: 178° horizontal, 178° vertical Gross (lbs): 9.5  Backlight Life (Hours): 30,000  Panel Surface: Anti-glare, hard-coating (3H)  Compatibility: Net (kg): 2.8  PC Resolution (max): Up to 1920x1080 non-interlaced Gross (kg): 4.3  Mac® Resolution (max): Up to 1920x1080  Connector: Packaging (in.): 22.1 x 17.4 x 6.1  3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1), Power in(3-pin plug (CEE22))  Audio: Dimensions (metric) (WxHxD):  Physical (in.): 19.7 x 14.8 x 7.9  Physical Without Stand (in.): 19.7 x 11.9 x 1.8  Dimensions (metric) (WxHxD):  Packaging (mm): 562 x 443 x 155	
Viewing Angles: 178° horizontal, 178° vertical Gross (lbs): 9.5  Backlight Life (Hours): 30,000  Panel Surface: Anti-glare, hard-coating (3H)  Compatibility: Net (kg): 2.8  PC Resolution (max): Up to 1920x1080 non-interlaced Gross (kg): 4.3  Mac° Resolution (max): Up to 1920x1080  Connector: Packaging (in.): 22.1 x 17.4 x 6.1  3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1), Power in(3-pin plug (CEE22))  Audio: Physical (without Stand (in.): 19.7 x 11.9 x 1.8  Dimensions (metric) (WxHxD): 19.7 x 11.9 x 1.8  Physical Without Stand (in.): 562 x 443 x 155  Packaging (mm): 562 x 443 x 155	
Backlight Life (Hours): 30,000  Panel Surface: Anti-glare, hard-coating (3H)  Compatibility: Net (kg): 2.5  PC Resolution (max): Up to 1920x1080 non-interlaced Gross (kg): 4.3  Mac® Resolution (max): Up to 1920x1080  Dimensions (imperial) (WxHxD):  Connector: Packaging (in.): 22.1 x 17.4 x 6.1  3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1), Power in(3-pin plug (CEE22))  Audio: Physical (in.): 19.7 x 14.8 x 7.9  Physical Without Stand (in.): 19.7 x 11.9 x 1.8  Dimensions (metric) (WxHxD):  Packaging (mm): 562 x 443 x 155	
Panel Surface:  Anti-glare, hard-coating (3H)  Net (kg):  2.8  Compatibility:  PC Resolution (max):  Up to 1920x1080 non-interlaced  Mac® Resolution (max):  Up to 1920x1080  Dimensions (imperial) (WxHxD):  Packaging (in.):  Physical (in.):  Physical (in.):  Physical Without Stand (kg):  2.5  4.3  Dimensions (imperial) (WxHxD):  Physical (in.):  Physical (in.):  19.7 x 14.8 x 7.9  Physical Without Stand (in.):  19.7 x 11.9 x 1.8  Dimensions (metric) (WxHxD):  Packaging (mm):  562 x 443 x 155	
Compatibility:  PC Resolution (max):  Up to 1920x1080 non-interlaced  Mac* Resolution (max):  Up to 1920x1080  Dimensions (imperial) (WxHxD):  Packaging (in.):  22.1 x 17.4 x 6.1  Physical (in.):  Physical (in.):  Physical Without Stand (kg):  2.5  Gross (kg):  4.3  Dimensions (imperial) (WxHxD):  Packaging (in.):  19.7 x 14.8 x 7.9  Physical Without Stand (in.):  Physi	
PC Resolution (max): Up to 1920x1080 non-interlaced Gross (kg): 4.3  Mac* Resolution (max): Up to 1920x1080 Dimensions (imperial) (WxHxD):  Connector: Packaging (in.): 22.1 x 17.4 x 6.1  3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1), Power in(3-pin plug (CEE22))  Audio: Physical (in.): 19.7 x 14.8 x 7.9  Physical Without Stand (in.): 19.7 x 11.9 x 1.8  Dimensions (metric) (WxHxD):  Packaging (mm): 562 x 443 x 155	
Mac* Resolution (max):         Up to 1920x1080         Dimensions (imperial) (WxHxD):           Connector:         Packaging (in.):         22.1 x 17.4 x 6.1           3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1), Power in(3-pin plug (CEE22))         Physical (in.):         19.7 x 14.8 x 7.9           Physical Without Stand (in.):         19.7 x 11.9 x 1.8           Pimensions (metric) (WxHxD):         Packaging (mm):         562 x 443 x 155	
Connector:       Packaging (in.):       22.1 x 17.4 x 6.1         3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1), Power in(3-pin plug (CEE22))       Physical (in.):       19.7 x 14.8 x 7.9         Physical Without Stand (in.):       19.7 x 11.9 x 1.8         Dimensions (metric) (WxHxD):         Packaging (mm):	
3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1), Power in(3-pin plug (CEE22))  Audio:  Internal Speakers:  2-watt (x2)  Physical (in.):  19.7 x 14.8 x 7.9  Physical Without Stand (in.):  19.7 x 11.9 x 1.8  Dimensions (metric) (WxHxD):  Packaging (mm):  562 x 443 x 155	
Physical Without Stand (in.): 19.7 x 11.9 x 1.8  Audio: Internal Speakers: 2-watt (x2)  Power:  Packaging (mm): 562 x 443 x 155	
Physical Without Stand (in.): 19.7 x 11.9 x 1.8  Audio: Internal Speakers: 2-watt (x2)  Power:  Physical Without Stand (in.): 19.7 x 11.9 x 1.8  Dimensions (metric) (WxHxD):  Packaging (mm): 562 x 443 x 155	
Internal Speakers:  2-watt (x2)  Packaging (mm):  562 x 443 x 155	
Packaging (mm): 562 x 443 x 155 <b>Power:</b>	
Physical (mm): 499.7 x 375.1 x 200	
Eco Mode (optimized):  20W  Physical Without Stand (mm): 499.7 x 301.9 x 45.5	
Consumption (typical):  25W  General:	
Regulations: CE EMC, CB, RoHS Green BOM & RoHS DoC, REACH S Consumption (max): 27W and DoC, ErP, WEEE, US NRTL w/ CA, FCC-B w/ ICES003, ENERGY S	
EPEAT Silver, Mexico CoC, Mexico Energy	IAN,
Voltage: AC 100-240V (universal), 50-60Hz  PACKAGE CONTENTS: VA2259-smh monitor, Power cable, Audio of Cable, Quick Start Guide, ViewSonic Wizard CD.	able, VGA
Vencinated Lack Clate 1	
Recycle/Disposal: Please dispose of in accordance with local, stated federal laws.	e or
Physical Controls: 1, 2, Down, Up, Power Warranty: Three-year limited warranty on parts, labor and backling	ht
Auto Image Adjust, UPC: 766907836530	,
Contrast/Brightness, Input Select,	
On Screen Display: Information, Manual Image Adjust,	
Advanced Image Adjust, Setup  Menu, Memory Recall (See user guide for complete OSD functionality)  Awards:  Awards:	
Operating Conditions:	
Temperature: 32-104° F (0-40° C)	

Copyright © ViewSonic Corporation 2000-2017. All rights reserved. (08/16/2017 05:56 PM PST)

20-90%

Humidity (non-condensing):