
Single Digit LED Numeric Display LA-501 D / N Series

The LA-501DN series were designed to meet the need for 13mm single-digit numeric displays. These LED numeric displays use GaAsP on GaP (Red), GaP (Green) for the emitting material and are housed in an epoxy resin package. They are single-digit displays with a character height of 13.0mm.


Features

- 1) Height of character: 13.0mm
- 2) Common anode and common cathode configurations are available for each color.
- 3) High-efficiency reflectors are used to achieve a bright, clear display.
- 4) The package surface is painted black and the segments are colored the display color.


•Dimensions (Unit : mm)




•Pin assignments



•Internal circuit schematic







Selection guide

Emitting color Common	Red	Green
Anode	LA-501VD	LA-501MD
Cathode	LA-501VN	LA-501MN

•Absolute maximum ratings ($T_a = 25^{\circ}C$)

Parameter	Symbol	Red	Green	Unit
		LA-501VD / VN	LA-501MD / MN	
Power dissipation	P _D	480	480	mW
Power dissipation	P_D / seg	60	60	mW
Forward current	۱ _F	20	20	mA
Peak forward current	I _{FP}	60 *	60 *	mA
Reverse voltage	V _R	5	5	V
Operating temperature	T _{opr}	-25 ~ +75		
Storage temperature	T _{stg}	-30 ~ +85		

* Pulse width 1ms, duty 1 / 5

•Electrical and optical characteristics ($T_a = 25^{\circ}C$)

Parameter	Symbol	Conditions	Red		Green		Unit		
			Min.	Тур.	Max.	Min.	Тур.	Max.	
Forward voltage	V_{F}	$I_F = 10 \text{mA}$	-	2	2.8	-	2.1	2.8	V
Reverse current	I _R	$V_R = 3V$	-	-	100	-	-	100	μA
Peak wavelength	λρ	I _F =10mA	-	563	-	-	563	-	nm
Spectral line halfwidth	Δλ	I _F =10mA	-	40	-	-	40	-	nm

2/5

 $\ensuremath{\textcircled{}}$ Not designed for radiation resistance.

•Luminous intensity

Parameter	λρ	Туре	Min.	Тур.	Max.	Unit
Red	650	LA-501VD	5.6	16	-	mcd
neu	650	LA-501VN	5.6			
Green	560	LA-501MD	FC	16		mcd
Green	563	LA-501MN	5.6	16	-	

 \bigcirc Condition I_F=10mA

●Iv classification

Parameter	Туре	ltem	lv classification	Unit
	LA-501VD LA-501VN	"上"	5.6 to 11	mcd
		" M "	9.0 to 18	mcd
Red		" N "	14 to 28	mcd
		"P"	22 to 45	mcd
		" Q "	36 to (71)	mcd
	LA-501MD LA-501MN	"上"	5.6 to 11	mcd
		" M "	9.0 to 18	mcd
Green		" N "	14 to 28	mcd
		"P"	22 to 45	mcd
		" Q "	36 to (71)	mcd

 \bigcirc Condition I_F=10mA

•Electrical and optical characteristics curves





Fig.3 Relative Luminous Intensity







Fig.4 Ratio of Maximum Tolerable Peak Current vs. Pulse Duration



LA-501 D / N Series

•Electrical and optical characteristics curves




Fig.5 Derating



	Notes
1)	The information contained herein is subject to change without notice.
2)	Before you use our Products, please contact our sales representative and verify the latest specifica- tions.
3)	Although ROHM is continuously working to improve product reliability and quality, semicon- ductors can break down and malfunction due to various factors. Therefore, in order to prevent personal injury or fire arising from failure, please take safety measures such as complying with the derating characteristics, implementing redundant and fire prevention designs, and utilizing backups and fail-safe procedures. ROHM shall have no responsibility for any damages arising out of the use of our Poducts beyond the rating specified by ROHM.
4)	Examples of application circuits, circuit constants and any other information contained herein are provided only to illustrate the standard usage and operations of the Products. The peripheral conditions must be taken into account when designing circuits for mass production.
5)	The technical information specified herein is intended only to show the typical functions of and examples of application circuits for the Products. ROHM does not grant you, explicitly or implicitly, any license to use or exercise intellectual property or other rights held by ROHM or any other parties. ROHM shall have no responsibility whatsoever for any dispute arising out of the use of such technical information.
6)	The Products are intended for use in general electronic equipment (i.e. AV/OA devices, communi- cation, consumer systems, gaming/entertainment sets) as well as the applications indicated in this document.
7)	The Products specified in this document are not designed to be radiation tolerant.
8)	For use of our Products in applications requiring a high degree of reliability (as exemplified below), please contact and consult with a ROHM representative : transportation equipment (i.e. cars, ships, trains), primary communication equipment, traffic lights, fire/crime prevention, safety equipment, medical systems, servers, solar cells, and power transmission systems.
9)	Do not use our Products in applications requiring extremely high reliability, such as aerospace equipment, nuclear power control systems, and submarine repeaters.
10)	ROHM shall have no responsibility for any damages or injury arising from non-compliance with the recommended usage conditions and specifications contained herein.
11)	ROHM has used reasonable care to ensure the accuracy of the information contained in this document. However, ROHM does not warrants that such information is error-free, and ROHM shall have no responsibility for any damages arising from any inaccuracy or misprint of such information.
12)	Please use the Products in accordance with any applicable environmental laws and regulations, such as the RoHS Directive. For more details, including RoHS compatibility, please contact a ROHM sales office. ROHM shall have no responsibility for any damages or losses resulting non-compliance with any applicable laws or regulations.
13)	When providing our Products and technologies contained in this document to other countries, you must abide by the procedures and provisions stipulated in all applicable export laws and regulations, including without limitation the US Export Administration Regulations and the Foreign Exchange and Foreign Trade Act.
14)	This document, in part or in whole, may not be reprinted or reproduced without prior consent of ROHM.



Thank you for your accessing to ROHM product informations. More detail product informations and catalogs are available, please contact us.

ROHM Customer Support System

http://www.rohm.com/contact/