


**OX-601**

### Features

- 4-Pin SMD package
- Fast warm-up
- Frequency Range, 10 MHz to 40 MHz
- Standard freq: 10, 12.8, 20, 24.576, 25, 30.72 MHz,
- High Reliability (based on fully intergrated Design)
- Low Power

### Applications

- Base stations (5G & 4G)
- Test equipment
- Small Cell
- Military communication equipment
- Stratum 3
- SyncE; 1588


### Performance Specifications

| Frequency Stabilities <sup>1</sup> 10 to 40 MHz          |      |         |      |         |  |                      |
|--|------|---------|------|---------|--|----------------------|
| Parameter  | Min  | Typical | Max  | Units   | Condition  | Options <sup>5</sup> |
| vs. operating temperature range<br>(referenced to +25°C) | -20  |         | +20  | ppb     | -40 to +85°C   |                      |
|  | -10  |         | +10  | ppb     | -40 to +85°C   |                      |
|  | -20  |         | +20  | ppb     | -40 to +95°C   |                      |
| slope  | -2   |         | +2   | ppb/°C  | @ Temp stab. +-10ppb   |                      |
| Initial tolerance  | -0.5 |         | +0.5 | ppm     | at time of shipment, nominal EFC   |                      |
| vs. supply voltage change                                | -10  | ±3      | +10  | ppb     | V <sub>c</sub> ±5% static  |                      |
| vs. load change  | -10  | ±2      | +10  | ppb     | Load ±5% static  |                      |
| vs. aging / day  | -5   | ±2      | +5   | ppb     | after 30 days of operation   |                      |
| vs. aging / year   | 500  |         | +500 | ppb     | after 30 days of operation   |                      |
| vs. aging / 10 years                                     | -3   |         | 3    | ppm     | after 30 days of operation   |                      |
| Holdover drift   |      |         | 5    | ppb     | over 24 hours, constant temperature (<±1°C) ;<br>after 30 days continous operation   |                      |
| Start up time  |      |         | 200  | msec    |  |                      |
| Warm-up time   |      |         | 3    | minutes | to ±50ppb of final frequency (1 hour reading)<br>@ +25°C   |                      |
| Loop bandwidth for wander<br>generation compliance       | 3    |         |      | mHz     | MTIE compliant with GR-1244 Fig 5-5<br>TDEV compliant with GR- 1244 Fig 5-4 ;<br>measurement setup: oscillator stabilized 24<br>hours at Constant Temperature (±1°C, still<br>air), data collected over 100,000 seconds at 1<br>second intervals (-3dB cutoff, 1st order high<br>pass loop filter) |                      |

## Performance Specifications

| Supply Voltage (Vs)        |                            |         |       |        |                            |         |
|----------------------------|----------------------------|---------|-------|--------|----------------------------|---------|
| Parameter                  | Min                        | Typical | Max   | Units  | Condition                  |         |
| Supply voltage (standard)  | 3.135                      | 3.3     | 3.465 | VDC    |                            |         |
| Power consumption          |                            | 1.3     | 1.5   | Watts  | during warm-up             |         |
|                            |                            | 0.4     | 0.5   | Watts  | steady state @ +25°C       |         |
| RF Output                  |                            |         |       |        |                            |         |
| Signal [standard]          | LVHCMOS                    |         |       |        |                            |         |
| Load                       |                            | 15      |       | pF     |                            |         |
| Signal Level (Vol)         |                            |         | 0.4   | VDC    | with Vs=3.3V and 15pF Load |         |
| Signal Level (Voh)         | 2.97                       | 3.3     |       | VDC    | with Vs=3.3V and 15pF Load |         |
| Duty Cycle                 | 45                         |         | 55    | %      | @ (Voh-Vol)/2              |         |
| Ron                        |                            | 26.5    |       | Ω      |                            |         |
| Roff                       |                            | 22      |       | Ω      |                            |         |
| Frequency Tuning (EFC)     |                            |         |       |        |                            |         |
| Tuning Range               | Fixed OCXO; No adjust      |         |       |        |                            |         |
| Additional Parameters      |                            |         |       |        |                            |         |
| Phase Noise <sup>3</sup>   |                            | -99     | -90   | dBc/Hz | 10 Hz                      | @ 20MHz |
|                            |                            | -125    | -120  | dBc/Hz | 100 Hz                     |         |
|                            |                            | -145    | -140  | dBc/Hz | 1 kHz                      |         |
|                            |                            | -155    | 150   | dBc/Hz | 10 kHz                     |         |
|                            |                            | -160    | -155  | dBc/Hz | 100kHz                     |         |
| Weight                     |                            |         | 1.0   | g      |                            |         |
| Processing & Packing       | Handling & Processing Note |         |       |        |                            |         |
| Absolute Maximum Ratings   |                            |         |       |        |                            |         |
| Supply voltage (Vs)        |                            |         | 3.8   | V      | with Vs=3.3 VDC            |         |
| Output Load                |                            |         | 50    | pF     |                            |         |
| Operable Temperature Range | -40                        |         | +95   | °C     |                            |         |
| Storage Temperature Range  | -40                        |         | +125  | °C     |                            |         |

## Outline Drawing / Enclosure




| OX-601     |                |
|------------|----------------|
| Height "H" | cover material |
| 4.1        | plastic        |

| Pin Connections |                                     |
|-----------------|-------------------------------------|
| 1               | I.C (Do not connect) / EFC (option) |
| 2               | Ground (Case)                       |
| 3               | RF Output                           |
| 4               | Supply Voltage Input                |

Recommended Pad  
Layout

# Standard Shipping Method (OX-601)



|   |   |
|---|---|
| <b>Maßangaben in mm:</b><br>A, B und K Maße von Bauelement abhängig<br>Fertigungstoleranzen entsprechen der DIN IEC 286-3 | <b>Dimension in mm:</b><br>A, B und K are dependent upon component dimensions<br>production tolerance complying DIN IEC 286-3 |
|---|---|

All dimensions in millimeters unless otherwise stated


| Enclosure Type  | Tape Width W (mm) | Quantity per meter | Quantity per reel | Dimension P |
|-----------------|-------------------|--------------------|-------------------|-------------|
| OX-601 (4.1 mm) | 24                | 83.3               | 850               | 12          |

## Reflow Profile

TP: max 250°C (@ solder joint, customer board level)  
 Tp: max: 10...40 sec

**Additional Information:**  
 This SMD oscillator has been designed for pick and place reflow soldering


SMD oscillators must be on the top side of the PCB during the reflow process.



## Additional Environmental Conditions

| Parameter                      | Description  |
|--------------------------------|--|
| Temperature Cycling            | JESD22-A104-D Cond.G - 500cycles -40/+125C;cycle time 30min  |
| Vibration, Sine                | MIL-STD-883 Meth 2007 Cond A - 20g 20-2000Hz 4x in each 3 axis 4min sweep time   |
| Mechanical Shock               | MIL-STD-202 Meth 213B Cond. F - 1500g 0,5ms 6 shocks in each direction   |
| Solderability                  | J-STD-002C Cond. A, Trough hole device; Cond.B, SMD ( correspond to MIL-STD-883 Meth 2003) - 255C (diving Time 5 0,5sec.) Dip&Look with 8h damp pre-treatment: solder wetting >95% |
| Solvent resistance             | MIL-STD-883 Meth 2003) - 255C (diving Time 5 0,5sec.) Dip&Look with  |
| ESD                            | 8h damp pre-treatment: solder wetting >95%   |
| Moisture Sensit.               | JESD22-A113-B - only if > MSL 1  |
| RoHS compliance                | 100% RoHS 6 compliant  |
| Washable                       | non-washable device  |
| High temp operating life(HTOL) | MIL-STD-202 Meth108A Cond C - 1000h @ 105C power on  |
| Low temp operating life(LTOL)  | IEC 60068-2-1 Cond. Ae - 1000h @ -40C power on   |

# Ordering Information



**Notes:**

1. Contact factory for improved stabilities or additional product options. Not all options and codes are available at all frequencies.
2. Unless other stated all values are valid after warm-up time and refer to typical conditions for supply voltage, frequency control voltage, load, temperature (25°C).
3. Phase noise degrades with increasing output frequency.
4. Subject to technical modification.
5. Contact factory for availability.



Microsemi, a wholly owned subsidiary of Microchip Technology Inc. (Nasdaq: MCHP), offers a comprehensive portfolio of semiconductor and system solutions for aerospace & defense, communications, data center and industrial markets. Products include high-performance and radiation-hardened analog mixed-signal integrated circuits, FPGAs, SoCs and ASICs; power management products; timing and synchronization devices and precise time solutions, setting the world's standard for time; voice processing devices; RF solutions; discrete components; enterprise storage and communication solutions, security technologies and scalable anti-tamper products; Ethernet solutions; Power-over-Ethernet ICs and midspans; as well as custom design capabilities and services. Learn more at [www.microsemi.com](http://www.microsemi.com).

**Microsemi Headquarters**  
 One Enterprise, Aliso Viejo, CA 92656 USA  
 Within the USA: +1 (800) 713-4113  
 Outside the USA: +1 (949) 380-6100  
 Sales: +1 (949) 380-6136  
 Fax: +1 (949) 215-4996  
 email: [sales.support@microsemi.com](mailto:sales.support@microsemi.com)  
[www.microsemi.com](http://www.microsemi.com)


Microsemi makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Microsemi assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by Microsemi have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by Microsemi hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. Microsemi does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information. Information provided in this document is proprietary to Microsemi, and Microsemi reserves the right to make any changes to the information in this document or to any products and services at any time without notice.

©2018 Microsemi, a wholly owned subsidiary of Microchip Technology Inc. All rights reserved. Microsemi and the Microsemi logo are registered trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.

# typical performance data


## typical warm up (frequency vs. time)

@ OX-6011-EAE-1080-20M000




## typical current consumption during power on

@ OX-6011-EAE-1080-20M000




## typical power consumption vs. operating temperature

@ OX-6011-EAE-1080-20M000



## typical frequency vs. temperature stability


@ OX-6011-EAE-1080-20M000



# typical performance data


## typical frequency vs. load change

@ OX-6011-EAE-1080-20M000




## typical frequency vs. supply voltage

@ OX-6011-EAE-1080-20M000



## typical frequency. vs cycled airflow without additional cover

@ OX-6011-EAE-1080-20M000



## typical frequency. vs cycled airflow with additional cover

@ OX-6011-EAE-1080-20M000

