

Touch panel - HTP104T/12015040/024/02050 - 2895255

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Mobile touch panel with 26.4 cm (10.4") graphics-capable TFT display, 65,535 colors, 800 x 600 pixels, 1 x Ethernet incl. accessories, and integrated NetCap remote control software.

Product Features

- Hand-held operator panel with software for on-site visualization or multi-user operation
- All-round protection (IP65)
- Suitable for drops from up to 1 m
- 3-stage enable switch, with key switch as an option, and/or stop button
- 3-stage enable switch, with key switch as an option, and/or stop button

Key commercial data

Packing unit	1 PCE
Weight per Piece (excluding packing)	444.44 GRM
Custom tariff number	84713000
Country of origin	Germany

Technical data

Dimensions

External dimension, width	311 mm
External dimension, height	281 mm
External dimension, depth	135 mm

Display

Display	26.4 cm/10.4" TFT
Resolution	800 x 600 Pixel (SVGA)
Backlighting	CCFL
Display backlight MTBF	50000 h
Touch screen	Resistive industrial touch screen
Operating Buttons on the Front	3-stage enable switch (2-channel), integrated in the handle
Colors	65,536 colors

Touch panel - HTP104T/12015040/024/02050 - 2895255

Technical data

Computer data

Processor	Xscale® PXA255, 400 MHz
RAM	64 MByte SDRAM
Mass storage	32 MByte flash memory
Interfaces	without
Network	1x Ethernet (10/100 Mbps), RJ45
Operating systems	Windows CE 5.0
Power consumption	17 VA

General

Weight	3.2 kg
--------	--------

Ambient conditions

Degree of protection	IP65
Ambient temperature (operation)	0 °C ... 50 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Permissible humidity (operation)	20 % ... 85 % (no condensation)
Permissible humidity (storage/transport)	10 % ... 85 % (no condensation)

Classifications

eCl@ss

eCl@ss 4.0	27330202
eCl@ss 4.1	27330202
eCl@ss 5.0	27242215
eCl@ss 5.1	27242391
eCl@ss 6.0	27249290
eCl@ss 7.0	27249290

ETIM

ETIM 2.0	EC001426
ETIM 3.0	EC001426
ETIM 4.0	EC001427
ETIM 5.0	EC001427

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404

Touch panel - HTP104T/12015040/024/02050 - 2895255

Classifications

UNSPSC

UNSPSC 13.2	43201404
-------------	----------