

Micro Commercial Components



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 (818) 701-4939 Fax:

FRA801G **THRU** FRA807G

8 Amp Glass **Passivated Fast Recovery Rectifier** 50 to 1000 Volts

- High Reliability
- High Surge Current Capability Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates RoHS Compliant. See ordering information)
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0 and MSL Rating 1 Marking: Type number
- Halogen free available upon request by adding suffix "-HF"

- Mounting Torgue: 5 in-lbs Maximum
- Operating Temperature: -55°C to +150°C Storage Temperature: -55°C to +150°C
- Typical Thermal Resistance: 3.0 °C/W junction to case


MCC Part Number	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
FRA801G	50V	35V	50V
FRA802G	100V	70V	100V
FRA803G	200V	140V	200V
FRA804G	400V	280V	400V
FRA805G	600V	420V	600V
FRA806G	800V	560V	800V
FRA807G	1000V	700V	1000V

Hectrical Characteristics @25°C Unless Otherwise Specified

			I
Average Forward Current	I _{F(AV)}	8 A	Tc = 100°C
Peak Forward Surge Current	I _{FSM}	150A	8.3ms, half sine
Maximum Instantaneous Forward Voltage	V _F	1.3V	I _{FM} = 8.0A
Maximum DC Reverse Current At Rated DC Blocking Voltage	I _R	5.0μA 100μA	T _A = 25°C T _A = 125°C
Maximum Reverse Recovery Time FRA801G-804G FRA805G FRA806G-807G	T _{rr}	150ns 250ns 500ns	I _F =0.5A, I _R =1.0A, I _{RR} =0.25A
Typical Junction Capacitance	C _J	60pF	Measured at 1.0MHz, V _R =4.0V

Notes: 1. High Temperature Solder Exemption Applied, see EU Directive Annex 7.

TO-220AC




DIMENSIONS					
	INCHES		ММ		
DIM	MIN	MAX	MIN	MAX	NOTE
Α	.560	.625	14.22	15.88	
В	.380	.420	9.65	10.67	
С	.100	.135	2.54	3.43	
D	.230	.270	5.84	6.86	
F		.250		6.35	
G	.500	.580	12.70	14.73	
Н	.190	.210	4.83	5.33	
Ī	.020	.045	0.51	1.14	
J	.012	.025	0.30	0.64	
K	.139	.161	3.53	4.09	Ø
L	.140	.190	3.56	4.83	
M	.045	.055	1.14	1.40	
N	.080	.115	2.03	2.92	


www.mccsemi.com


FRA801G thru FRA807G





FIG.1- REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM



















www.mccsemi.com

2 of 3



Ordering Information

Device	Packing
(Part Number)-BP	Bulk;1Kpcs/Box

Note: Adding "-HF" suffix for halogen free, eg. Part Number-BP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

Revision: B 3 of 3 2013/01/01