

Time-saving embedded tools

MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

PowerBank 2 Click





PID: MIKROE-4116

The **PowerBank 2 Click** is a Click board[™] equipped with the <u>RT9480</u>, highly integrated and easy to use power solution for Li-ion power bank and other powered handheld applications. It's usually called EZPBS (Easy to Use PowerBank Solution). This single chip includes a linear charger, a synchronous Boost with dual output load management and a torch function support. The battery volume and the state of charging and discharging can be indicated by 4 LEDs.

PowerBank 2 Click is supported by a mikroSDK compliant library, which includes functions that simplify software development. This Click boardTM comes as a fully tested product, ready to be used on a system equipped with the mikroBUSTM socket.

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system. ISO 14001: 2015 certification of environmental management system. OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).



MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

Specifications

Туре	Battery charger
Applications	Sub-Battery Applications, Power-Bank Applications for Smartphones, Tablets and Other Portable Devices
On-board modules	RT9480
Key Features	Power solution for Li-ion power bank and other powered handheld applications, a synchronous Boost with dual output load management and a torch function support, designed for single- cell Li-ion or Li-polymer batteries
Interface	12C
ClickID	No
Compatibility	mikroBUS
Click board size	L (57.15 x 25.4 mm)
Input Voltage	5V

Resources

<u>mikroBUS</u>™

<u>mikroSDK</u>

Click board[™] Catalog

Click Boards™

Downloads

PowerBank 2 click 2D and 3D files

PowerBank 2 click example on Libstock

RT9480 datasheet

PowerBank 2 click schematic

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system. ISO 14001: 2015 certification of environmental management system. OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).