## SPECIFICATION CONTROL DRAWING

**CHEMINAX** 

75 OHM, AWG 30, 7 STRANDS OF 38 AWG, COAXIAL CABLE

Date	4-30-07
Revision	A

7530A1817


THIS SPECIFICATION SHEET FORMS A PART OF THE LATEST ISSUE OF RAYCHEM SPECIFICATION 1200.

## CONSTRUCTION DETAILS

**ELECTRICAL CHARACTERISTICS** 

DIMENSIONS ARE NOMINAL VALUES IN INCHES UNLESS OTHERWISE DESIGNATED

CHARACTERISTIC IMPEDANCE 75 ± 3 ohms, Method B CAPACITANCE 17.5 pF/ft. (nominal) VELOCITY OF PROPAGATION 77% (nominal)



# **ADDITIONAL REQUIREMENTS**

for 1000 ft.

#### **ELECTRICAL**

CONDUCTOR RESISTANCE 255. ohms/1000 ft. (nominal) 10,000 megohms (minimum) **INSULATION RESISTANCE** 

JACKET FLAWS

1.0 kV (rms) SPARK TEST IMPULSE TEST 6.0 kV (peak)

VOLTAGE WITHSTAND (DIELECTRIC) 1000 volts (rms) (minimum)

**SHIELD** .071 AWG 38 Tin-Coated Copper **JACKET** .097 Zerohal\*

#### **ENVIRONMENTAL**

**FLAMMABILITY** Method B **HEAT SHOCK** 225°C

LOW TEMPERATURE-COLD BEND -30°C/2.75 inch mandrel

VOLTAGE WITHSTAND 1000 volts (rms) (minimum) (Post Environmental)

### **PHYSICAL**

INSULATION (DIELECTRIC)

**ELONGATION** 50% (minimum)

TENSILE STRENGTH 1000 lbf/in2 (minimum)

JACKET

**ELONGATION** 150% (minimum) TENSILE STRENGTH 1200 lbf/in2 (minimum) JACKET THICKNESS .013 inch (nominal) 90% (minimum)

SHIELD COVERAGE

Designate outer jacket color with a dash number in accordance

with MIL-STD-681. Other codes and suffixes may be added to the part number, as necessary, to capture any additional requirements imposed by the purchase order.

\* is a trademark of Tyco Electronics Corporation.

Outer jacket color will be black (designated by a "-0" appended

to the part number, e.g. 7530A1817-0) unless otherwise

WEIGHT 6.7 lbs/1000 ft. (nominal)

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.



specified.