

## Monitor - VL 19" LCD RTOUCH (S) FPM - 2400047

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



19-inch/48 cm flat panel LCD monitor with resistive touch screen. Includes two rear USB ports

### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 STK    |
| Weight per Piece (excluding packing) | 1.000 g  |
| Custom tariff number                 | 85299020 |
| Country of origin                    | Taiwan   |

### Technical data

#### Note

|                         |   |
|-------------------------|---|
| Utilization restriction | EMC: class A product, see manufacturer's declaration in the download area |
|-------------------------|---|

#### Display

|                   |                                   |
|-------------------|-----------------------------------|
| Display           | 48.3 cm/19" TFT                   |
| Screen resolution | 1280 x 1024 Pixel(s) (SXGA)       |
| Backlighting      | LED                               |
| Touch technology  | Resistive industrial touch screen |
| Colors            | 16.7 million colors               |

#### Monitor data

|         |                 |
|---------|-----------------|
| Network | Without network |
| Slots   | without slots   |

#### General

|               |                    |
|---------------|--------------------|
| Mounting type | Front installation |
| Weight        | 9 g                |

#### Ambient conditions

|                                 |                           |
|---------------------------------|---------------------------|
| Degree of protection            | IP65 (front), IP20 (back) |
| Ambient temperature (operation) | 0 °C ... 55 °C            |

## Monitor - VL 19" LCD RTOUCH (S) FPM - 2400047

### Technical data

#### Ambient conditions

|  |  |
|--|--|
| Ambient temperature (storage/transport)  | -40 °C ... 70 °C                             |
| Permissible humidity (storage/transport) | 5 % ... 95 %                                 |
| Vibration (operation)                    | DIN EN 60068-2-6                             |
| Shock                                    | 15g, 11 ms in accordance with IEC 60068-2-27 |

#### Device supply

|                   |               |
|-------------------|---------------|
| Power supply unit | 24 V DC ±20 % |
|-------------------|---------------|

#### Standards and Regulations

|                       |  |
|-----------------------|--|
| Shock                 | 15g, 11 ms in accordance with IEC 60068-2-27 |
| Vibration (operation) | DIN EN 60068-2-6                             |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 5.1 | 27242402 |
| eCl@ss 6.0 | 19200201 |
| eCl@ss 8.0 | 19200403 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001425 |
| ETIM 4.0 | EC001428 |
| ETIM 5.0 | EC001428 |

#### UNSPSC

|              |          |
|--------------|----------|
| UNSPSC 12.01 | 43211902 |
|--------------|----------|