


THIS DRAWING AND THE INFORMATION SET FORTH HEREON ARE THE PROPERTY OF TYCO ELECTRONICS CORPORATION AND ARE TO BE HELD IN TRUST AND CONFIDENCE. PUBLICATION, DUPLICATION, DISCLOSURE OR USE FOR ANY PURPOSE NOT EXPRESSLY AUTHORIZED IN WRITING BY TYCO ELECTRONICS CORPORATION IS PROHIBITED.

REVISION

REV	DESCRIPTION	DATE
D	REVISED PER DCR MP03090	4/28/03

If this document is printed it becomes uncontrolled.
Check for the latest revision.



PART NUMBER	"A" THREAD	øB ±.02	øC REF	øJ		P REF REC	T REF	PANEL THK ⁴
				MIN EXP	MAX REC			
CES-2-T1-XX	1-12 UNF	.75 [19,05]	1.41 [35,82]	.40 [10,16]	.11 [2,79]	2.25 [57,15]	.21 [5,33]	1/4 [6,35]
CES-2-T1B-XX	1-12 UNF	.75 [19,05]	1.41 [35,82]	.60 [15,24]	.17 [4,31]	2.75 [69,85]	.21 [5,33]	1/4 [6,35]
CES-3-T1-XX	1 3/8-12 UNF	1.10 [27,94]	1.91 [48,52]	.60 [15,24]	.17 [4,31]	2.75 [69,85]	.31 [7,88]	1/4 [6,35]
CES-4-T1-XX	2-8 UN	1.56 [39,62]	2.72 [69,09]	.90 [22,86]	.30 [7,62]	3.15 [80,01]	.31 [7,88]	3/8 [9,65]
CES-5-T4-XX	3 3/8-8 UN	2.90 [73,66]	4.10 [104,14]	1.25 [31,75]	.50 [12,7]	4.50 [114,30]	.31 [7,88]	1/2 [12,7]

NOTES:

1. THE LAST "XX" IN THE PART NUMBER DESIGNATES MATERIAL AS SHOWN BELOW:
 "AL": ALUMINUM 6061 T-6 WITH FINISH OF HARD ANODIZE PER MIL-A-8625, TYPE III, CLASS 2, DYED BLACK.
 "SS": STAINLESS STEEL TYPE 316, WITH FINISH OF PASSIVATE PER QQ-P-35, OR MIL-S-5002 FOR STANDARD BLACK NYLON MATERIAL, OMIT THE LAST "XX" IN THE PART NUMBER.
 2. HEAT SHRINKABLE BOOT MATERIAL IN ACCORDANCE WITH -3 POLYOLEFIN
 3. PART TO BE MARKED AS SHOWN, REPLACE X'S WITH APPROPRIATE CHARACTERS. (e.g. CES-2-T1-AL).
 4. THIS PART IS DESIGNED TO FIT THROUGH A PANEL OR BULKHEAD WITH A MAXIMUM WALL THICKNESS AS INDICATED IN TABLE.
4. FACTORY APPLIED HOT MELT ADHESIVE IS STANDARD.

SPECIFICATION CONTROL DRAWING		
tyco Electronics	Tyco Electronics Corporation 300 Constitution Drive Menlo Park, CA, USA 94025	Product Brand: Raychem
TITLE CABLE ENTRY SEALS 3 ENTRY, STANDARD		
SIZE A	CODE IDENT. NO. 06090	DWG. NO. CES-X-TX-XX
DO NOT SCALE THIS DRAWING		SHEET 1 OF 1