

## Accessories - MSTBC-MT 0.2-0.5 - 1879531

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Module socket contact, is inserted into the plug housing MSTBC after crimping the conductor, for conductors from 0.2 to 0.5 mm<sup>2</sup>



### Key commercial data

Packing unit	1
Minimum order quantity	100
GTIN	 4 017918 269067
Custom tariff number	85366990
Country of origin	GERMANY

### Technical data

#### Technical data

Nominal current	9 A (with 0.5 mm <sup>2</sup> conductor cross section)
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Max. conductor cross section, stranded	0.5 mm <sup>2</sup>

#### Connection data

Core diameter including insulation	1.15 mm ... 2.31 mm
Stripping length of individual wires	3 mm

#### Material data

Contact material	CuFe
Contact surface material	Tin-plated

### Classifications

#### eclass

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701

# Accessories - MSTBC-MT 0.2-0.5 - 1879531

## Classifications

### eclass

eCl@ss 6.0	27260704
eCl@ss 7.0	27440402

### etim

ETIM 3.0	EC001121
ETIM 4.0	EC001121

### unspsc

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121410
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

## Drawings

### Dimensioned drawing

