

Specification Sheet

Part Number: CTP380STD

Split side is ideal for applications where braided tubing or spiral wrap may be difficult to install.

Tubing provides full coverage where spiral wrap or other coverings may not be suitable.

In harsh applications the tubing provides resistance to crushing, impact, and abrasion.

Tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat, cold, and sunlight on cables and wires.



Convoluted Tubing, Slit, 0.38" Dia, PE, Black, 1900 ft/carton

Article Number 169-60515

Type CTP380

Color Black (BK)

Quantity Per carton

| | |
|--------------------------------|---|
| Product Description | HellermannTyton's Convoluted Tubing, also known as Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offers excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires. |
| Short Description | Convoluted Tubing, Slit, 0.38" Dia, PE, Black, 1900 ft/carton |
| Global Part Name | CTP380-PE-BK |
| Length L (Imperial) | 1900.0 |
| Length L (Metric) | 579.1 |
| Variant | Slit |
| Inner Diameter D (Imperial) | 0.380 |
| Inner Diameter D (Metric) | 9.65 |
| Diameter D (Imperial) | 0.526 |
| Diameter D (Metric) | 13.36 |
| Outside Diameter OD (Imperial) | 0.526 |
| Outside Diameter OD (Metric) | 13.36 |
| Nominal Diameter (Imperial) | 0.38 |

| | |
|------------------------------|----------------------------------|
| Nominal Diameter (Metric) | 9.65 |
| Wall Thickness WT (Imperial) | 0.005 |
| Wall Thickness WT (Metric) | 0.127 |
| Material | Polyethylene (PE) |
| Material Shortcut | PE |
| Halogen Free | No |
| UV Resistant (Yes/No) | No |
| Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 1900 |
| Package Quantity (Metric) | 579.12 |
| Customs Number | 3926909988 |

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)