Aug.1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved. In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

			٥	<u>5</u>																										
CL NO.(OLD)	HG HIROSE	Note QT:Qualification Test	(WITHOUT BULK REUnless otherwise specified, refer to JIS C 5402.	Manufacture Point	NOTE. NEASU	SOLDERABILITY	RESISTANCE TO SOLDERING HEAT		(STEADY STATE)	RAPID CHANGE OF TEMPERATURE	ENVIRONMENTAL	FORCE	SHOCK	VIBHALION	MECHANICAL OPERATION	INSERTION AND WITHDRAWAL FORCES		VOLTAGE PROOF	INSULATION RESISTANCE	CONTACT RESISTANCE 1 mA (DC OR	MAHRING		CONSTRUCTION		ට	RATING VO	OPERATING TEMPERATL	APPLICABLE STANDARD	> [COUNT DESCRI
DRAW	ELECTRIC	Test AT:Assurance Test	(WITHOU ecified, refer to J		MEASUREMENT POINT O	SOLDERED.	SOLDER TEI	MIST EXPOSED IN 48 h.	EXPOSED AT			APPLY 68.6 DIRECTION.	490 m/s² DU AT 3 TIME	AMPLITUDE FOR 3 DIF	1000 TIMES		CHARACTERISTICS	300 V AC F	100 V DC.		CONFIRMED VISUALLY.	Įž			CURRENT	VOLTAGE	OPERATING TEMPERATURE RANGE	ANDARD		DESCRIPTION OF REVISIONS
ELC4-045469-0	LTD.	{ _	(WITHOUT BULK RESISTANCE refer to JIS C 5402.		POINT OF CONTACT RESISTANCE	SOLDERED AT SOLDER TEMPERATURE, 245 ± 2 °C FOR IMMERSION, DURATION 3 ± 1 S.	SOLDER TEMPERATURE, 20	1 5 % SALT WA	T 40 °c, 90~95		CHARACTERISTICS	APPLY 68.6 N PULL FORCE TO THE MATING DIRECTION.	490 m/s² DURATION OF PUL NT 3 TIMES FOR 3 DIRE	TUDE 0.75 mm, — 3 DIRECTIONS.	INSERTIONS /	BY APPLICABLE		AC FOR 1 min.		(DC OR 1000 Hz).	ON VISUALLY.	ND BY MEASURIN	IEST METHOD	• I	0.5 A	125 V AC ,	- 25 °C TO			s ву снко
469-01	SPECIFICATION	O:Applicable Test	$ a = a \cdot a $	S Hamera		PERATURE, 245± TION 3±1S.	260±5°C FOR 10±1'S.	WATER SPRAY FOR	5 %, 96 h.	30 -		O THE MATING	PULSE 11 ms DIRECTIONS.	m/s ² AT 2 h,	ID EXTRACTIONS	CONNECTOR.				₽		NG INSTRUMENT.		SPECIFICATIONS	4	175 V DC	60 °C		> [DATE CO
CL23	SHEET PART NO.		10 03 12 10	5 dame ga	DESIGNED		NO DEFORMATION OF CASE EXCESSIVE LOOSENESS OF TERMINALS.		① INSULATION RESISTANC 1 MΩ MIN. (AT HIGH 100 MΩ MIN. (AT DRY. ② NO DAMAGE, CRACK AND OF PARTS.	DAMAGE, PARTS.		① REMAIN ENGAGED WHILI IS APPLIED. ② NO DEFECT AT MATING ATTHE TEST.	OF PARTS.	① NO ELECTRICAL DISCONT 10 # s. ② NO DAMAGE, CRACK AND				NO FLASHOVER OR BREAKDOWN.	250 MΩ MIN.	35 mΩ MAX.		ACCORDING TO DRAWING.	HEQ.		APPLICABLE CABLE	OPERATING HUMIDITY RANGE	STORAGE TEMPERATURE RANGE			COUNT DESCRIPTION OF REVISIONS
1-3001-4-50	3110-8S(50)		63.12.11 03.12.12	T. Wateraby X. Misson		LDER IMM)VERED N	N OF CASE AND SENESS OF THE	OSION.	 ① INSULATION RESISTANCE: 1 MΩ MIN. (AT HIGH HUMIDITY.) 100 MΩ MIN. (AT DRY.) ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS. 	CRACK AND LOOSENESS,		3AGED WHILE THE FORCE AT MATING AREA AFTER		 (1) NO ELECTRICAL DISCONTINUITY OF 10 µs. 2) NO DAMAGE, CRACK AND LOOSENESS 				OR BREAKDOWN.				DRAWING.	REQUIREMENTS			%	OI ၁°			ВУ
1/1)		2	<u> </u>	D RELEASED	0	0	0	-, O -	s, O –		IR O -	0	ESS,	ESS, O -	0	⊢ ⊦	-+	0	00	00		QIIAI			%	റ്			CHKD DATE