

Label - MM-EML (17,5X8)R C1 YE/BK - 1116203

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Label, Roll, yellow/black, unlabeled, can be labeled with: THERMOMARK GO, mounting type: adhesive, lettering field size: 17.5 x 8 mm, Number of individual labels: 297

Product Description

The MM-EML... polyester self-adhesive labels are available as pre-punched material for equipment marking.

Your advantages

- ✓ The pre-punched geometry enables easy and convenient use
- ✓ Thanks to the innovative material composition, each label can be printed which results in zero wastage
- ✓ Easy and efficient material cartridge system: Includes both the material to be printed and the corresponding ink ribbon
- ✓ No visible difference between retrospective marking and existing markings created with a desktop roll printer
- ✓ The pre-punched self-adhesive labels are particularly suitable for the professional and permanent marking of various components and equipment in control cabinet, controller, and systems manufacturing
- ✓ The material is cUL certified
- ✓ High-quality and solvent-resistant marking solution for industrial applications that is created by means of thermal transfer printing



Key Commercial Data

| | |
|----------------------|---|
| Packing unit | 1 pc |
| GTIN |  4 063151 041779 |
| GTIN | 4063151041779 |
| Custom tariff number | 96121010 |
| Country of origin | China |

Technical data

Dimensions

| | |
|------------|------|
| Length (b) | 7 mm |
|------------|------|

Label - MM-EML (17,5X8)R C1 YE/BK - 1116203

Technical data

Dimensions

| | |
|-----------|---------|
| Width (a) | 17.5 mm |
|-----------|---------|

Ambient conditions

| | |
|---------------------------------|---|
| Ambient temperature (operation) | -40 °C ... 150 °C |
| Recommended storage conditions | 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended. |

General

| | |
|-----------------------------|--|
| Color | yellow/black |
| Components | free from silicone, halogen, and cadmium |
| Material | Polyester |
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| Number of individual labels | 297 |
| Marking mounting type | adhesive |

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 9.0 | 27400629 |
|------------|----------|

Approvals


Approvals

Approvals

cULus Recognized

Ex Approvals

Approval details

| | | | |
|------------------|---|---|---------|
| cULus Recognized |  | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | MH48542 |
|------------------|---|---|---------|

