

C14 Male to C13 Female Splitter, PDU Style - C14 to 2x C13, 10A, 250V, 18 AWG, 6 ft. (1.83 m), Black

MODEL NUMBER: P004-006-2C13









C14-to-C13 splitter allows 2 devices with C14 inlets to share one AC power input cord and one C13 outlet on a PDU or UPS system.

Features

C14-to-C13 Y-Style Splitter Cord Connects 2 Devices with C14 Inlets to One C13 OutletThis IEC-320-C14 to IEC-320-C13 splitter allows two devices with C14 power inlets to share one AC input cord and one C13 outlet. This C14 male to C13 female cord features a C14 end for connecting to an AC power source and two C13 ends for connecting to devices. By connecting two devices to one outlet, the power cord splitter frees up space in a PDU, UPS system or surge protector and helps reduce cable clutter. The 6-ft. (1.83 m) length allows you flexibility in placing equipment with respect to the power outlet.

Dual IEC Cable Powers a Wide Variety of Essential ElectronicsWith this PC power splitter, a single C13 outlet can power two devices, such as computers, monitors, printers, instrument amplifiers and other equipment compatible with a C13 connector. Ideal for areas where AC outlets are limited, such as rack cabinets, this dual IEC cable is compatible with power and extension cords.

Highlights

- Connects 2 devices to one AC outlet to save space and reduce cable clutter
- Recommended for powering dual computers, monitors or other compatible peripherals
- 6-ft. (1.83 m) length allows flexibility in placing devices in relationship to AC outlet
- Ideal replacement for worn-out or missing C13-to-C14 PDUstyle extension cord

Applications

- Connect 2 devices like computers, monitors, scanners and printers to one power outlet up to 6-ft. (1.83 m) away in your home office, work space or dorm room
- Cut cable clutter by powering both monitors in a dual-monitor display mount with a single cord
- Save space in a 0U vertical rack-mount PDU by plugging two rack devices into one outlet

Package Includes

 P004-006-2C13 C14 Male to C13 Female Splitter, PDU Style, 6-ft. (1.83 m), Black

Specifications

OVERVIEW		
UPC Code	037332154750	
Device Compatibility	Computer; Monitor/HDTV; Printer; Scanner; UPS; PDU	
Country/Region	Global	
INPUT		
Maximum Input Amps	10	
Voltage Compatibility (VAC)	100-250	



Plug Color Black Cable Jacket Color Black Cable Jacket Material PVC Cable Jacket Material PVC PV		
Gable Jacket Color Black Cable Jacket Material PVC Cable Jacket Rating VW-1 Power Cord Jacket Type SJT Cable Outer Diameter (OD) 7.8mm Number of Conductors 3 Wire Gauge (AWG) 18 Wire Gauge (AWG) 18 Wire Gauge (OD - mm²) 0.82 Cable Length (ft) 6 Cable Length (ft) 1.83 Shipping Dimensions (ftwd / in.) 1.0.00 x 7.00 x 0.50 Shipping Dimensions (ftwd / in.) 25.40 x 17.78 x 1.27 Shipping Weight (libx) 0.73 Shipping Weight (libx) 0.33 Serviron Ministrat Operating Temperature Range -4" to 140°F (-20" to 60°C) Storage Temperature Range -4" to 140°F (-20" to 60°C) Operating Temperature Range 10% to 65% RH CONNECTIONS Side A - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage Yes Locking Plug No Colled Power Cord No STANDARDS & COMPLIANCE	PHYSICAL	
Cable Jacket Material PVC Cable Jacket Rating VW-1 Power Cord Jacket Type SJT Cable Outer Diameter (OD) 7.8mm Number of Conductors 3 Number of Conductors 3 Wire Gauge (AWG) 18 Wire Gauge (OD - mm²) 0.82 Cable Length (ft.) 6 Cable Length (ft.) 6 Cable Length (m) 1.83 Shipping Dimensions (ftwd / rm) 1.80 Shipping Dimensions (ftwd / rm) 25.40 x 17.78 x 1.27 Shipping Dimensions (ftwd / rm) 25.40 x 17.78 x 1.27 Shipping Weight (bs.) 0.73 Shipping Weight (bs.) 0.73 Shipping Pemperature Range 4* to 140*F (-20* to 80*C) Storage Temperature Range 4* to 140*F (-20* to 60*C) Operating Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1	Plug Color	Black
Cable Jacket Rating VW-1 Power Cord Jacket Type SJT Cable Outer Diameter (OD) 7.8mm Number of Conductors 3 Wire Gauge (AWG) 18 Wire Gauge (AWG) 0.82 Cable Length (ft.) 6 Cable Length (ft.) 6 Cable Length (fm) 18.3 Shipping Dimensions (Inwd / in.) 10.00 x 7.00 x 0.50 Shipping Dimensions (Inwd / om) 25.40 x 17.78 x 1.27 Shipping Weight (Ibs.) 0.73 Shipping Weight (kg) 0.33 ENVIRONMENTAL Operating Temperature Range 4° to 140°F (-20° to 60°C) Storage Temperature Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 (2) IEC-320-C13 FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage Yes Locking Plug No Colled Power Cord No STANDARDS & COMPLIANCE	Cable Jacket Color	Black
Power Cord Jacket Type SJT Cable Outer Diameter (OD) 7.8mm Number of Conductors 3 Wire Gauge (AWG) 18 Wire Gauge (OD - mm²) 0.82 Cable Length (HL) 6 Cable Length (m) 1.83 Shipping Dimensions (twd / in.) 10.00 x 7.00 x 0.50 Shipping Dimensions (twd / cm) 25.40 x 17.78 x 1.27 Shipping Weight (bs.) 0.73 Shipping Weight (kg) 0.33 ENVIRONMENTAL Operating Temperature Range -4" to 140°F (-20" to 60°C) Operating Humidity Range 10% to 65% RH Storage Temperature Range 10% to 65% RH CONNECTIONS Side B - Connector 1 IEC-320-C14 Side B - Connector 1 (2) IEC-320-C13 FEATURES & SPECIFICATIONS Antibacterial Antibacterial No Angled Plug No High Youtage Yes Locking Plug No Coiled Power Cord No	Cable Jacket Material	PVC
Cable Outer Diameter (OD) 7.8mm Number of Conductors 3 Wire Gauge (AWG) 18 Wire Gauge (OD - mm²) 0.82 Cable Length (It) 6 Cable Length (m) 1.83 Shipping Dimensions (hwd / in.) 10.00 x 7.00 x 0.50 Shipping Dimensions (hwd / cm) 25.40 x 17.78 x 1.27 Shipping Weight (kg) 0.33 ENVIRONMENTAL Operating Temperature Range -4" to 140"F (-20" to 60"C) Storage Temperature Range -4" to 140"F (-20" to 60"C) Operating Humidity Range 10% to 65% RH Storage Humidity Range CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 (2) IEC-320-C13 FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage Yes Locking Plug No Coiled Power Cord No	Cable Jacket Rating	VW-1
Number of Conductors 3 Wire Gauge (AWG) 18 Wire Gauge (OD - mm²) 0.82 Cable Length (ft.) 6 Cable Length (m) 1.83 Shipping Dimensions (hwd / in.) 10.00 x 7.00 x 0.50 Shipping Dimensions (hwd / cm) 25.40 x 17.78 x 1.27 Shipping Weight (lbs.) 0.73 Shipping Weight (kg) 0.33 ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 (2) IEC-320-C13 FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage Yes Locking Plug No Colled Power Cord No STANDARDS & COMPLIANCE	Power Cord Jacket Type	SJT
Wire Gauge (AWG) 18 Wire Gauge (DD - mm²) 0.82 Cable Length (ft.) 6 Cable Length (m) 1.83 Shipping Dimensions (hwd / in.) 10.00 x 7.00 x 0.50 Shipping Dimensions (hwd / cm) 25.40 x 17.78 x 1.27 Shipping Weight (lbs.) 0.73 Shipping Weight (kg) 0.33 ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 [2] IEC-320-C13 FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage Yes Locking Plug No Colled Power Cord No STANDARDS & COMPLIANCE	Cable Outer Diameter (OD)	7.8mm
Wire Gauge (OD - mm²) 0.82 Cable Length (ft.) 6 Cable Length (m) 1.83 Shipping Dimensions (hwd / in.) 10.00 x 7.00 x 0.50 Shipping Dimensions (hwd / cm) 25.40 x 17.78 x 1.27 Shipping Weight (lbs.) 0.73 Shipping Weight (kg) 0.33 ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side B - Connector 1 IEC-320-C14 Side B - Connector 1 (2) IEC-320-C13 FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage Yes Locking Plug No Coiled Power Cord No	Number of Conductors	3
Cable Length (ft.) 6 Cable Length (m) 1.83 Shipping Dimensions (hwd / in.) 10.00 x 7.00 x 0.50 Shipping Dimensions (hwd / om) 25.40 x 17.78 x 1.27 Shipping Weight (lbs.) 0.73 Shipping Weight (kg) 0.33 ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 (2) IEC-320-C13 FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage Yes Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE	Wire Gauge (AWG)	18
Cable Length (m) 1.83 Shipping Dimensions (hwd / in.) 10.00 x 7.00 x 0.50 Shipping Dimensions (hwd / cm) 25.40 x 17.78 x 1.27 Shipping Weight (lbs.) 0.73 Shipping Weight (kg) 0.33 ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 (2) IEC-320-C13 FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage Yes Locking Plug No Coiled Power Cord No	Wire Gauge (OD - mm²)	0.82
Shipping Dimensions (hwd / in.) 10.00 x 7.00 x 0.50 Shipping Dimensions (hwd / cm) 25.40 x 17.78 x 1.27 Shipping Weight (lbs.) 0.73 Shipping Weight (kg) 0.33 ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 (2) IEC-320-C13 FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage Yes Locking Plug No Colled Power Cord No	Cable Length (ft.)	6
Shipping Dimensions (hwd / cm) 25.40 x 17.78 x 1.27 Shipping Weight (kg) 0.73 ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 (2) IEC-320-C13 FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage Yes Locking Plug No Colied Power Cord No	Cable Length (m)	1.83
Shipping Weight (lbs.) 0.73 Shipping Weight (kg) 0.33 ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 (2) IEC-320-C13 FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage Yes Locking Plug No Colled Power Cord No	Shipping Dimensions (hwd / in.)	10.00 x 7.00 x 0.50
Shipping Weight (kg) ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 (2) IEC-320-C13 FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage Yes Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE	Shipping Dimensions (hwd / cm)	25.40 x 17.78 x 1.27
ENVIRONMENTAL Operating Temperature Range	Shipping Weight (lbs.)	0.73
Operating Temperature Range	Shipping Weight (kg)	0.33
Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 (2) IEC-320-C13 FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage Yes Locking Plug No Coiled Power Cord No	ENVIRONMENTAL	
Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 (2) IEC-320-C13 FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage Yes Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE	Operating Temperature Range	-4° to 140°F (-20° to 60°C)
Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 (2) IEC-320-C13 FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage Yes Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE	Storage Temperature Range	-4° to 140°F (-20° to 60°C)
CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 (2) IEC-320-C13 FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage Yes Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE	Operating Humidity Range	10% to 65% RH
Side A - Connector 1 IEC-320-C14 Side B - Connector 1 (2) IEC-320-C13 FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage Yes Locking Plug No Coiled Power Cord No	Storage Humidity Range	10% to 65% RH
FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage Yes Locking Plug No Coiled Power Cord No	CONNECTIONS	
FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage Yes Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE	Side A - Connector 1	IEC-320-C14
Antibacterial No Angled Plug No High Voltage Yes Locking Plug No Coiled Power Cord No	Side B - Connector 1	(2) IEC-320-C13
Angled Plug No High Voltage Yes Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE	FEATURES & SPECIFICATIONS	
High Voltage Yes Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE	Antibacterial	No
Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE	Angled Plug	No
Coiled Power Cord No STANDARDS & COMPLIANCE	High Voltage	Yes
STANDARDS & COMPLIANCE	Locking Plug	No
	Coiled Power Cord	No
	STANDARDS & COMPLIANCE	
Product Certifications CSA (Canada); cUL Listed; UL Listed	Product Certifications	CSA (Canada); cUL Listed; UL Listed



Product Compliance	RoHS; REACH
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	Lifetime limited warranty



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.