
For 1AG, 3AG, 7AG, 8AG THRU HOLE MOUNT TYPES

WITH SNAP-IN PC LEGS



MATERIAL: .020 (.51) thick Brass, Tin Plate **Current Rating:** 15 Amps


CAT. NO. 3513



MATERIAL:

.020 (.51) thick Brass, Tin Plate **Current Rating: 15 Amps**

CAT. NO.	A	В
3515	.060 (1.5)	.060 (1.5)
3515P	.060 (1.5)	.093 (2.4)
3516P	.060 (1.5)	.120 (3.0)




With or Without Orientation Legs

WITH STRAIGHT PC LEGS



MATERIAL:

.020 (.51) thick Brass, Tin Plate **Current Rating: 15 Amps**



Mounting Detail

.270 [6.9]

WITH STRAIGHT PC LEGS


WITH SNAP-IN PC LEGS



MATERIAL:

.020 (.51) thick Brass, Tin Plate **Current Rating: 15 Amps**

CAT. NO.	Н	L	END STOPS
3510	.421 (10.7)	.140 (3.6)	NO
3529	.421 (10.7)	.140 (3.6)	YES
3511	.430 (10.9)	.250 (6.4)	NO
3514	.430 (10.9)	.250 (6.4)	YES



Mounting Detail .300 [7.6] .067 [1.70] DIA. S

CAT. NO. 3530

WITH SOLDER LUG

For 1AG, 3AG, 7AG, 8AG




LOW PROFILE



MATERIAL:

.020 (.51) thick Brass, Nickel Plate **Current Rating: 15 Amps**


CAT. NO.	A	В
3533	Flat	.656 (16.7)
3535	45°	.562 (14.3)
3570	-	NO TAB





MATERIAL:

.020 (.51) thick Brass, Nickel Plate **Current Rating:** 15 Amps





CAT. NO. 3531 (Without End Stops)


WITH QUICK-FIT TAB



MATERIAL:

.020 (.51) thick Brass, Nickel Plate **Current Rating: 15 Amps**

CAT. NO.	Α		В	
4246	.020	(0.5)	.187	(4.7)
4247	.020	(0.5)	.205	(5.2)
4244	.032	(0.8)	.250	(6.4)




WITH OR WITHOUT END STOPS



MATERIAL:

.020 (.51) thick Brass, Nickel Plate **Current Rating:** 15 Amps

CAT. NO.	END STOPS
3532	YES
3567	NO



Tel (718) 956-8900 • Fax (718) 956-9040 (800) 221-5510 • kec@keyelco.com

KEYSTONE Rohs Compliant - ISO 9001 CERTIFIED