




TagLock™ Snap-On Securing Device for 120V Breakers

Catalog #: 148689, 148693 & 148694

Design

- Designed for 120v circuit breaker switches that have holes in the switch tongue
- Quick and easy - First snap device into place by positioning the smaller rectangular cavity around the breaker switch if it fits; otherwise position the larger opening.
- Secure with 50 lb. minimum strength non-releasable nylon fasteners as shown, or padlock
- Dual cavities accommodate different sized switch tongues, and durable metal pins add additional security



Material

- Body - Glass filled Nylon
- Color: Red (PMS 1805C)
- Dowel pin: Stainless Steel
- Fasteners - Nylon
- UL Rating: UL 94 – HB

Chemical	°C	Chemical	°C
Acetone	25	Petroleum	25
Acetone	60	Turpentine oil	25
Chlorine, chlorine water	25	Turpentine substitute (white spirit)	25
Fuel, engine: Gasoline (normal & premium grade)	85	Trichloroethane 1,1,1	45
Lubrication oil: gear oil	< 120	Lubricating oil: HD engine oils, hydraulic oils, transformer oils	< 120
Fuel, engine: M15 mixture (15% methanol)	70	Water (including seawater)	25
Methanol	25	Water (including seawater), chlorinated (<0,5 mg/l)	80


Temperature Range

- Nylon 66: -20° to 120°C (-4° to 250°F)

Chemical Resistance
All approved chemicals listed are based on the manufactures specified chemical resistance chart for plastic material only.

Dimensions

A	0.620" [15.8mm]
B	1.006" [25.6mm]
C	2.696" [68.5mm]
D	0.293" [7.4mm]
E	2.159" [54.8mm]



Circuit Breaker Cross Reference Guide

Circuit Breaker Manufacture	Breaker Type	" of Poles
Bryant	BR	1
Challenger	C	1
Cutler Hammer	BAB	1
Cutler Hammer	BD	1
Cutler Hammer	BR	1
Cutler Hammer	BRH	1
Cutler Hammer	CH	1
Cutler Hammer	CHB	1
Cutler Hammer	CHP	1
Cutler Hammer	CL	1
Cutler Hammer	HBAW	1
Cutler Hammer	HBAX	1
Cutler Hammer	HQP	1
Cutler Hammer	QBHW	1
Cutler Hammer	QC	1
Cutler Hammer	QCD	1
Cutler Hammer	QCHW	1
Cutler Hammer	QHCW	1
Cutler Hammer	QHCX	1
Cutler Hammer	QHPW	1
Cutler Hammer	QHPX	1
Cutler Hammer	QPHW	1
General Electric	THHQB-A	1
General Electric	THHQC-A	1
General Electric	THHQL-A	1
General Electric	THQB-A	1
General Electric	THQC-A	1
General Electric	THQL-A	1
General Electric	TQB-A	1
General Electric	TQC-A	1
General Electric	TQL-A	1

Circuit Breaker Manufacture	Breaker Type	" of Poles
Siemens ITE	BL	1
Siemens ITE	BLH	1
Siemens ITE	BQ	1
Siemens ITE	BQH	1
Siemens ITE	HBL	1
Siemens ITE	HBQ	1
Siemens ITE	HQP	1
Siemens ITE	HQPP	1
Siemens ITE	QP	1
Siemens ITE	QPH	1
Siemens ITE	QPP	1
Siemens ITE	QPPH	1
Square D	QO	2-3
Square D	QOB	2-3
Square D	QOB-VH	1
Square D	QO-SWN	2-3
Square D	QO-VH	2-3
Westinghouse	BA	1-3
Westinghouse	BAB	1-3
Westinghouse	BR	1-3
Westinghouse	HBAW	1
Westinghouse	HBAX	1
Westinghouse	HQP	1
Westinghouse	QBHW	1
Westinghouse	QC	1
Westinghouse	QCHQ	1
Westinghouse	QHCW	1
Westinghouse	QHCX	1
Westinghouse	QHPW	1
Westinghouse	QPHW	1
Westinghouse	WPHX	1

MSDS Information

1. HAZARDS IDENTIFICATION

This product is NOT DANGEROUS and contains no hazardous ingredients.

2. FIRST AID MEASURES/HEALTH INFORMATION /PROTECTION

Eye Contact:	Not applicable, product is inert
Ingestion:	Not applicable, first aid is not normally required.
Inhalation:	Not applicable
Skin Contact:	Not applicable, product is inert, except if product is melted use gloves. For hot melted product, immerse in or flush affected area with water to dissipate heat, and then obtain medical attention.
Exposure Limits:	None
Threshold Limits	None
Personal Protection:	None (ambient conditions)
NPCA-HMIS Rating:	Health: 0; Flammability: 1; Reactivity: 0
NFPA-704 Rating:	Health: 0; Flammability: 1; Reactivity: 0

3. FIRE-FIGHTING MEASURES

<ul style="list-style-type: none"> Be cautious of hot melted Nylon 	<ul style="list-style-type: none"> Use water spray to cool fire, exposed surfaces, and to protect personnel
<ul style="list-style-type: none"> Isolate product from fire 	<ul style="list-style-type: none"> Respiratory and eye protection is required for fire fighting personnel
<ul style="list-style-type: none"> Extinguish fire with water spray 	<ul style="list-style-type: none"> Decomposition products under fire conditions: Oxygen-lean conditions may cause monoxide and irritating smoke

4. ACCIDENTAL RELEASE MEASURES

Land	Recover material and place in suitable container for reuse or for disposal in conformance with local regulations.
Water	Recover material and place in suitable container for reuse or for disposal in conformance with local regulations.

5. HANDLING AND STORAGE

5.1 Handling	5.2 Storage
No precautions noted-see local regulation if needed	Storage pressure: Atmospheric
	Storage temperature: Ambient, no direct sunlight

6. EXPOSURE CONTROLS/PERSONAL PROTECTION

6.1 Exposure limit values	6.2 Exposure Controls
None	6.2.1 Occupational Exposure Controls
	6.2.1.1 Respiratory Protection: Not applicable
	6.2.1.2 Hand Protection: Not applicable
	6.2.1.3 Eye Protection: Not applicable
	6.2.1.4 Skin Protection: Not applicable
	6.2.2 Environmental Exposure Controls: No data available

7. PHYSICAL AND CHEMICAL PROPERTIES

General Information	
Other Information	

8. STABILITY AND REACTIVITY

8.1 Conditions to Avoid
Higher Temperatures and direct sunlight (chemical resistance is excellent)
Highly stable, but temperatures over 480 F may cause degradation
8.2 Materials to Avoid
No data available
8.3 Hazardous Decomposition Products
Under fire and oxygen-lean conditions may cause monoxide and irritating smoke

MSDS Information (continued)

9. ECOLOGICAL INFORMATION

9.1 Ecotoxicity	No data available
9.2 Mobility	No data available
9.3 Persistence and Degradability	No data available
9.4 Bioaccumulative Potential	No data available
9.5 Other Adverse Effects	No data available

10. DISPOSAL CONSIDERATIONS

None of the materials in this product are Recyclable, dispose of all materials in accordance with an applicable federal, state, and local law.
--

11. TRANSPORT INFORMATION

No data available

12. REGULATORY INFORMATION

This product has been tested and validated to the Regulatory Requirements listed below:	
● OSHA 29 CFR 1910.147 ©(4)(ii)(A)(1)/(c)(5)(ii)(C)(1)	● ANSI Standard Z244

13. OTHER INFORMATION

No data available

WARRANTY STATEMENT

Supplier warrants that all goods will be free from defects in materials and workmanship for a period of six (6) months from the time of delivery to the consumer by Supplier. Repair, replacement or credit (at Supplier’s option) upon return of the goods is Purchaser’s sole remedy for any such losses, expenses, inconveniences or damages. The limited warranty does not apply if (1) the defect is the result of use or handling of the goods in a manner, circumstance, or purpose other than those approved or instructed by Supplier, as identified in the installation procedures accompanying the product, the instruction for use found on the product and as found on the Brady’s website; or (2) the goods are misused or abused or there is evidence of tampering, mishandling, neglect, accidental damages, modifications or repair without the approval of Supplier.

Copyright 2019 Brady Worldwide, Inc. | All Rights Reserved
 Material may not be reproduced or distributed in any form without written permission.