



**DB25 AND XLRM WIRING CHART**

XLR (CHANNEL)	CABLE (COLOR)	PIN 2 (RED)	PIN 3 (BLACK)	PIN 1 (BARE)
1	BROWN	24	12	25
2	RED	10	23	11
3	ORANGE	21	9	22
4	YELLOW	7	20	8
5	GREEN	18	6	19
6	BLUE	4	17	5
7	PURPLE	15	3	16
8	GRAY	1	14	2

PART NO.	CABLE LENGTH "X"
DB25M02XLRM	2.00 FT +/- 1.50 IN
DB25M03XLRM	3.00 FT +/- 1.50 IN
DB25M10XLRM	10.00 FT +/- 1.50 IN

**NOTES:**

1. BREAKOUT CABLE LENGTH: 18.00 +/- 0.75 INCHES. SEE TABLE FOR COLOR.

**B** 2. THIS PRODUCT COMES COILED AND PACKAGED IN BAG.

**B** 3. JACKSCREWS ARE SHIPPED UNASSEMBLED. CABLE COMES WITH BOTH #4-40 THREAD (2) AND #M3 THREAD (2) JACKSCREWS.

**B** 4. MATERIALS:  
 XLR MALE CONNECTOR:  
 HANDLE - ZINC ALLOY, NICKEL PLATED  
 HOUSING - ZINC ALLOY, NICKEL PLATED  
 INSULATOR - THERMOPLASTIC, GREEN  
 CONTACT PINS - COPPER ALLOY, SILVER PLATED  
 H.S. TUBING - THERMOPLASTIC  
 DSUB - COPPER ALLOY, NICKEL PLATED WITH GOLD PINS  
 JACKSCREWS - STAINLESS STEEL

5. THIS PRODUCT IS RoHS COMPLIANT.

**CUSTOMER DRAWING**

REVISIONS					UNLESS OTHERWISE SPECIFIED 1. ALL DIMENSIONS IN INCHES - TWO PLACE DECIMALS ±0.02 - THREE PLACE DECIMALS ±0.005	THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.						
REV	ECO NUMBER	DATE	BY	APVD		SIZE	WIDTH	MULT	LBS/M	TEMPER		
C	26795	7-8-11	TO	TJK	DO NOT SCALE DRAWING	FINISH SPEC No.				MATERIAL SPEC No.		
B	26637	10/11/10	RS	TJK		FIRST USED ON				SCALE 2:1		
A	25716	10/03/07	JGK	TJK		DATE DRAWN	BY	CHKD	APVD			
						9/12/06	JGK	RS	TJK			
					NAME DB25M TO 8 XLR MALES, RoHS					PART No. DB25M__XLRM		REV C