
PAIR	CONSISTS OF:
FG-30723-S21	(2) FG-23629-S2I


BOTH MICROPHONES OF THE PAIR ARE TESTED TO THEIR RESPECTIVE 2.1 SHEET AND THEN MATCHED TO THE OTHER MICROPHONE USING THE SPECIFICATION AND CONDITIONS BELOW:

FREQUENCY	TEST TYPE	RANGE OF DEVIATION BETWEEN MICROPHONES	UNITS
200 Hz	PHASE	2.0 MAX.	DEGREES
500 Hz	SENSITIVITY	I.O MAX.	dBV

## NOTES:

- I. DC SUPPLY VOLTAGE 1.3 VOLTS.
- 2. TESTED WITH NO LOAD COUPLED TO THE OUTPUT.
- 3. SENSITIVITY AND PHASE VALUES INDICATED ARE VALID AT 50% RH.





BLACK STRIPE SHOWS MICROPHONE WITH GREATER RESPONSE PHASE VALUE AT 200Hz.

RED CONTROLLED

Revision	C.O. #	Implementation Date	RELEASE LEVEL	REVISION
				A
			l Active I	ΙД
А	M10103025	8-17-09		/ \

8-17-09

8-20-09

DATE

8-20-09

APP. BY

SHT 2.1

KNOWLES ELECTRONICS ITASCA, ILLINOIS U.S.A.

WHEN TEST LIMITS ARE USED TO ESTABLISH INCOMING INSPECTION ACCEPTANCE/REJECTION CRITERIA, CORRELATION OF TEST EQUIPMENT WITH KNOWLES IS ALSO REQUIRED FOR ELIMINATION OF EQUIPMENT AND TEST METHOD VARIATION				
MATCHED PAIR FG-30723-S2	1 GJP			

PERFORMANCE SPECIFICATION

FG-30723-S21		KNOWLES ELECTRONICS		FG-30723-S21		1		
Sheet	4.	. 1		ITASCA, ILLINOIS U.S.A.		Sheet 4	1.1	
Dr. Ch. App.	By LSY GJP GJP	Date 8-17-09 8-20-09 8-20-09	Subje	MATCHED PAIR MICROPHONES  Revision		Release Level  Active		
	COL. I		2	3		4	No.	No.
	Part or Dwg. no.		Tot. Req.	Nomenclature:		Applicable Specs or Remarks	l tem	Line
FG-2362	29-521		2	MICROPHONE ASSEMBLY				Ι

## RED CONTROLLED

REVISION A c.o. MI0103025

FG-30723-S21 Sheet 4.1

PROPRIETARY NOTE: THIS DOCUMENT CONTAINS INFORMATION WHICH IS THE PROPRIETARY PROPERTY OF KNOWLES ELECTRONICS, LLC. OR ITS AFFILIATED ENTITIES. IT IS ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED, COPIED, USED, OR DISCLOSED TO ANY THIRD PARTY PARTIALLY OR WHOLLY IN ANY MANNER WITHOUT PRIOR WRITTEN PERMISSION OF, AND MUST BE RETURNED UPON REQUEST BY, KNOWLES ELECTRONICS, LLC.