

## Repeater - FB-PA/SC - 2316375

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



PROFIBUS PA interface module with oscilloscope

### Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	320.0 g
Custom tariff number	85176200
Country of origin	Netherlands

### Technical data

#### Dimensions

Width	25 mm
Height	100 mm
Depth	132 mm

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 60 °C
Ambient temperature (storage/transport)	-20 °C ... 60 °C
Degree of protection	IP20

#### General

Mounting position	On horizontal DIN rail NS 35 in acc. with EN 60715
Net weight	222 g
UL, USA / Canada	UL 508 Listed

#### Power supply

Supply voltage range	Supplied via backplane
Max. current consumption	12 mA
Connection method	Bus base module
Conductor cross section flexible max.	2.50 mm <sup>2</sup>
Conductor cross section flexible min.	0.20 mm <sup>2</sup>

## Repeater - FB-PA/SC - 2316375

### Technical data

#### Power supply

Conductor cross section solid max.	2.50 mm <sup>2</sup>
Conductor cross section solid min.	0.20 mm <sup>2</sup>
Conductor cross section AWG max.	12
Conductor cross section AWG min.	24

### Classifications

#### eCl@ss

eCl@ss 5.1	27242208
eCl@ss 6.0	27242208

#### ETIM

ETIM 5.0	EC001604
----------	----------