

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	54-00197	Connector, 6 pin M12 A-code plug, 12xL24mm, gold plated, panel mount, solder cup, IP67	1	nut and o-ring included
2	Wire	Wire, hook-up, TS, 24 AWG, UL 11028, 600V, 105C, 1.1 mm, mPPE	6	color: red, black, white, yellow, blue, green
3	Heat shrink	Heat shrink, UL, black	6	covers solder joints






Notes:

Cable rated for 30 V, 2 A Temperature: -40 ~ 105 °C

IP67 waterproof rating when mated with corresponding (IP67) connector and installed properly in panel

Cables individually packaged in PE bag Functionally equivalent components may be substituted



Wiring Diagram						
54-00197	wire color (P/N)					
1	red (30-01762)					
2	yellow (30-01765) black (30-01763)					
3						
4	white (30-01764)					
6	blue (30-01766)					
7	green (30-01767)					

Revision:	Date:	Description:	Prepared: Digitally signed by PB	Notes:						
Α	11/7/2022	Initial release	PB Date: 2022.12.01 08:47:29 -08'00'	RoHS compliant		TENSILITY				
			Verified: MP Digitally signed by MP Date: 2022.12.01 10:00:59 -08'00'	Function test: no open, no short circuit, no intermittent	tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com					
			Dimensions are in			10x 1.3-1.3231202 Web terisinty.com				
			millimeters.	Describtion.			Part nur	mber:		
			Tolerances: X: ± 0.5 mm	Cable, 305 mm, M12 6C plug panel mount 54-00197 to blunt cut, 24 AWG, UL 11028 hook-up wire	Α	10-05267				
			X.X: ± 0.3 mm X.XX: ± 0.05 mm		Scale:	1:1		Sheet 1 of 1		

3