

# 3M™ Finesse-it™ Roloc™ Finishing Disc Pad



- Enables use of 3M<sup>TM</sup> Hookit<sup>TM</sup> buffing pads with the 3M<sup>TM</sup> Roloc<sup>TM</sup> backup pad
- Hook-and-loop system provides quick and easy pad attachment and removal
- Compressibility of the foam provides conformability
- Roloc<sup>TM</sup> quick change attachment system provides fast pad change out for multi-step finishing processes

## **Specifications**

Attribute Name V	/alı	ue
------------------	------	----

 $\begin{array}{ll} \text{Attachment Type} & \text{Hookit}^{\text{TM}} \\ \text{Brand} & \text{Finesse-it}^{\text{TM}} \end{array}$ 

Color Yellow

Converted Form Backup Pads, Disc

Density Rating Firm
Diameter 3 Inch
Diameter (Metric) 76.2 mm

Equipment - Machines Disc Sanders, Right Angle Grinders

Form Type Roloc<sup>TM</sup>

Hook Type 2, 3

Industries AOEM, Paint Preparation

Max OPM 10000 Max RPM 6000

Product Form Backup Pad

 $\begin{array}{ll} \text{Thickness} & 1 \text{ Inch} \\ \text{Thickness (Metric)} & 25.4 \text{ mm} \\ \text{Thread Size} & \text{Roloc}^{\text{TM}} \text{ TR} \\ \text{Type} & \text{Regular} \end{array}$ 

### **Product Details**

- Enables use of 3M<sup>TM</sup> Hookit<sup>TM</sup> buffing pads with the 3M<sup>TM</sup> Roloc<sup>TM</sup> backup pad
- Hook-and-loop system provides quick and easy pad attachment and removal
- Compressibility of the foam provides conformability
- Roloc<sup>TM</sup> quick change attachment system provides fast pad change out for multi-step finishing processes
- Buffing pads are sold separately

3M<sup>TM</sup> Finesse-it<sup>TM</sup> Roloc<sup>TM</sup> Finishing Disc Pad is made with soft foam to provide greater conformability than standard 3M<sup>TM</sup> Roloc<sup>TM</sup> backup pads. The 3M<sup>TM</sup> Hookit<sup>TM</sup> surface is manufactured with mushroom headed hooks that hold the buffing pad firmly in place. This backup pad is designed to be used with rotary tools only. The foam backing provides good conformability.



Roloc<sup>TM</sup> attachment allows you to change pads with a simple twist

#### **Ouick and Easy Pad Attachment and Removal**

Our 3M<sup>TM</sup> Roloc<sup>TM</sup> TR quick change pads have a plastic threaded button or screw designed to easily and quickly attach to a Roloc<sup>TM</sup> TR product (sold separately) so that operators can conveniently change pads with a simple twist-off, twist-on motion. The Roloc TR system provides a secure attachment, and the variety of available Roloc sanding pads allows swapping from one application to the next in seconds.

### **About 3M<sup>TM</sup> Finesse-it<sup>TM</sup> Products**

3M<sup>TM</sup> Finesse-it<sup>TM</sup> products are a line of specially engineered abrasives, compounds, polishes, and buffing pads to be used on OEM and baked refinish paints to remove defects, sand scratches, or swirl marks on a variety of painted surfaces. 3M Finesse-it products are an integral part of a 3M recommended buffing system for repairing surface defects to clear coats, lacquered wood, solid surfaces, gelcoat, powder coat, industrial paint, acrylic, and glass.