


10 9 8 7 6 5 4 3 2 1



View on mating side



A = 48 STANDARD CONTACTS L=2

Marking	Standard
Performance level	G2/0 = Contact area perform. level 2 / Termination tin
Flux proof	NO
Fixing clip	NO
Dimensions	609-6043-201 SHT 1
Technical Data	PS-85013-0002

A	G2/0	a1-16, b1-16, c1-16
Contact symbol	Perform. level	Contact position number

EC NO: 12004-0363 DRWN:SSUDHIR 2004/03/11 CHKD:GJLOWE 2004/03/11 APPR:GJLOWE 2004/04/26	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	REVISE ON CAD ONLY	
	 = 0  = 0	mm	INCH	DIMENSION STYLE MM ONLY		TITLE 48 POS MALE CONNECTOR ACC DIN41612 STYLE R/2 CONTACTS ARRANGEMENT	
		4 PLACES	± ---	± ---	DRAWN BY SSUDHIR		DATE 2004/03/11
		3 PLACES	± ---	± ---	CHECKED BY GJLOWE		DATE 2004/03/11
	2 PLACES	± ---	± ---	APPROVED BY GJLOWE	DATE 2004/03/11	MATERIAL NO. 85013-9023 DOCUMENT NO. SDA-85013-9023 SHEET NO. 1 OF 1	
	1 PLACE	± ---	± ---	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			
		ANGULAR	± ---°	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			



A3

9 8 7 6 5 4 3 2 1