



SPC-10-8-SS

Ruland SPC-10-8-SS, 5/8" x 1/2" Rigid Coupling, 303 Stainless Steel, Two-Piece Clamp Style With Keyway, 1 5/16" OD, 2" Length



Description

Ruland SPC-10-8-SS is a two-piece rigid coupling with 0.6250" x 0.5000" bores, 1 5/16" OD, 2" length, and 3/16" x 1/8" keyways. SPC-10-8-SS has opposing hardware for a balanced design. Proprietary Nypatch® anti-vibration coating on hardware allows for even seating of the screw, repeated screw installations, prevents galling, and maintains high holding power. It eliminates the need to treat screws upon receipt greatly reducing installation time. Forged screws test beyond ANSI standards to ensure maximum holding power. Tightly controlled bore tolerance of +.002"/+.0005" is maintained. SPC-10-8-SS is made from 303 stainless steel with hardware of like material for consistent corrosion resistance. It is machined from solid bar stock that is sourced exclusively from North American mills and is RoHS3 and REACH compliant. SPC-10-8-SS is manufactured in our Marlborough, MA factory under strict controls using proprietary processes.

Product Specifications

| | | | |
|---------------------------------------|--|--|---|
| Bore (B1) | 0.6250 in | Small Bore (B2) | 0.5000 in |
| Keyway (K1) | 3/16 in | Keyway (K2) | 1/8 in |
| B1 Max Shaft Penetration | 1.000 in | B2 Max Shaft Penetration | 1.000 in |
| Outer Diameter (OD) | 1 5/16 in | Bore Tolerance | +0.0020 in / +0.0005 in |
| Length (L) | 2 in | Clearance Diameter (C) MAX | 1.514 in |
| Recommended Gap | 0.063 in | Recommended Shaft Tolerance | +0.0000 in / -0.0005 in |
| Forged Clamp Screw | #10-32 | Screw Material | 18-8 300 Series Stainless Steel with Nypatch® |
| Hex Wrench Size | 5/32 in | Screw Finish | Bright |
| Seating Torque | 45 lb-in | Screw Location (R) | 0.484 in |
| Number of Screws | 8 ea | Rated Torque | 475 in-lb |
| Moment of Inertia | 0.1442 lb-in ² | Maximum Speed | 4,000 RPM |
| Full Bearing Support Required? | No | Nypatch® Anti-Vibration Hardware? | Yes |
| Zero-Backlash? | Yes | Balanced Design | Yes |
| Material Specification | Type 303 Austenitic, Non-Magnetic Bar | Temperature | -40°F to 350°F (-40°C to 176°C) |
| Finish Specification | Bright, No Plating | Manufacturer | Ruland Manufacturing |
| Country of Origin | USA | Weight (lbs) | 0.562900 |
| UPC | 634529022238 | Tariff Code | 8483.60.8000 |
| UNSPC | 31163009 | | |
| Note 1 | Performance ratings are for guidance only. The user must determine suitability for a particular application. | | |
| Prop 65 | ⚠️ WARNING This product can expose you to the chemical Nickel (metallic), known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov . | | |

Installation Instructions

1. Align the SPC-10-8-SS two-piece rigid coupling on the two shafts to be connected. There should be no misalignment.
2. Tighten the Nypatch® screws in two stages, starting with the inside screws. Using a 5/32 in torque wrench, tighten the inside screws to 22.5 lb-in which is half the recommended seating torque. Repeat the process for the outside screws, tightening to half the recommended seating torque.
3. Be sure to maintain the gap of 0.063 in between the two halves during installation.
4. Tighten the screws to the full recommended seating torque of 45 lb-in following the same pattern,

- starting with the inside screws first.
5. For optimum results do not exceed the shaft penetration length of 1.000 in.
-