	2								1								
	Т	THIS COPY IS PROVIDED ON A RESTRICTED					N / R I PCORD	OTES: 1. DIAMET 2. DIMENS 3. FOR PA SHOWN, 4. CABLE dl & a	<ul> <li>DIAMETER DIMENSION SHOWN FOR REFERENCE ONLY.</li> <li>DIMENSIONS IN BRACKETS [ ] ARE ENGLISH.</li> <li>FOR PART NUMBERS AND LENGTHS OTHER THAN THOSE SHOWN, CONTACT YOUR PANDUIT SALES PERSON.</li> <li>CABLE MEETS REQUIRMENTS OF EUROCLASS B2ca, sla, d1 &amp; a1 PER EN 50575.</li> </ul>								
					<u></u>		FLAME RETARDANT	5. CABLE DECLARATION OF PERFORMANCE IS PAN-DOP-FA032. CABLE DESCRIPTION FIBER OPTIC INDOOR-OUTDOOR CENTRAL TUBE CABLE									
B							JACKET GEL-FILLED TUBE CONTAINING 12 -		PART NUMBERS AVAILABLE FIBER TYPE					JACKET RATING COLOR			
								FACC912						LSZH	BLACK	=	
								FACC612					n	LSZH	BLACK		
								FACC512					/2	LSZH	BLACK		
								FACCX12				0/125um ON		LSZH	BLACK	-	
							250um FIBERS.	FACCZ12						LSZH	BLACK		
									TECHNICAL SPECIFICATI					BEND RADIUS			
									MAXIMUM LOSS 3.5 dB/KM @ 850nm 1.5 dB/KM @ 1300nm SINGLEMODE MAXIMUM LOSS .75 dB/KM @ 1310nm .75 dB/KM @ 1500nm			INSTALLA		LONG	TERM	-	
								1.5				100 mm (3.9 in)			)mm 4 in)		
		7.7 DIA. [.30] REF.						SINGLE				TENSILE LOAD - LSZH RATED					
												INSTALLATION 1500 N (337.5 16f)		LONG TERM 700 N (157.5 lbf)			
									TEMPER								
								-20° C	-20°C TO +70°C -20°C			ATION TO +70°C -4		STORAGE -40°C TO +75°C		-	
								-4°F 1	-4°F TO +158°F -4°F			) +158° F	- 40°	F TO +	167° F		
									TITLE			INDOOR-					
									WITH 12 FIBERS IN A CE customer drawing								
									TTEM REVISION NAME MO2432DU/00								
									DATASET FILE NAME MO2432DU_DC_12/OC				╡┣┦			T	
									UNLESS OTHERWISE SPEC			CIFIED.	PART NO.				
									.× :			± .010 [0.3]		FACC*12-14			
	00A 0	3-13-18	8-13-18 SAT WMA SKH INITIAL RELEASE			INITIAL RELEASE		M02432DU-DC-12				ITRD ANGLE		ng number: 102432DU - DC - 12		12	
	REV	EV DATE BY CHK APR			APR		DESCRIPTION	ECN	DRAWN BY DATE CHK SCALE SAT 03-13-18 WMA NONE			SHT 1 OF 1			SIZE A		
				-		2						1				,	