


MQS

TE Internal #: 1-1418775-1 Housing for Female Terminals, Wire-to-Wire / Wire-to-Board, 5 Position, .1 in [2.54 mm] Centerline, Black, Wire & Cable, Signal, MQS

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > MQS, CONNECTOR HOUSING



Connector & Housing Type: Housing for Female Terminals Mating Tab Width: .63 mm [.025 in]

Connector System: Wire-to-Board, Wire-to-Wire

Number of Positions: 5

Centerline (Pitch): 2.54 mm [.1 in]

All MQS, CONNECTOR HOUSING (571)

Features

Product Type Features

Connector Shape

Connector & Housing Type

Rectangular

Housing for Female Terminals

Connector System	Wire-to-Board, Wire-to-Wire
Sealable	No
Hybrid Connector	No
Primary Locking Feature	On the Terminal
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	5
Number of Rows	1
Electrical Characteristics	
Operating Voltage	12 VDC
Nominal Voltage Architecture	12 V, 24 V
Body Features	
Cable Exit Angle	180°
Primary Product Color	Black
Connector & Keying Code	Neutral

C For support call+1 800 522 6752

Housing for Female Terminals, Wire-to-Wire / Wire-to-Board, 5 Position, .1 in [2.54 mm] Centerline, Black, Wire & Cable, Signal, MQS



Contact Features

Contact Size	.63mm
Contact Type	Receptacle
Mating Tab Width	.63 mm[.025 in]
Contact Current Rating (Max)	7.5 A
Mechanical Attachment	
Terminal Position Assurance	Yes
Strain Relief	Without
Mating Alignment Type	Polarized
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PBT GF
Centerline (Pitch)	2.54 mm[.1 in]
Dimensions	
Connector Height	4.5 mm[.177 in]
Product Width	16.5 mm[.65 in]

Usage Conditions

Operating Temperature (Max)	120 °C[248 °F]
Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94HB
Packaging Features	
Packaging Method	Box
Other	
Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

Housing for Female Terminals, Wire-to-Wire / Wire-to-Board, 5 Position, .1 in [2.54 mm] Centerline, Black, Wire & Cable, Signal, MQS




EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-


Compatible Parts



Also in the Series | MQS

Housing for Female Terminals, Wire-to-Wire / Wire-to-Board, 5 Position, .1 in [2.54 mm] Centerline, Black, Wire & Cable, Signal, MQS







PCB Headers & Receptacles(214)

Customers Also Bought



Housing for Female Terminals, Wire-to-Wire / Wire-to-Board, 5 Position, .1 in [2.54 mm] Centerline, Black, Wire & Cable, Signal, MQS





Documents

Product Drawings 5POS MQS REC

English

CAD Files

Customer View Model ENG_CVM_CVM_1-1418775-1_A.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1418775-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1418775-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages Micro Quadlok Interconnection System (MQS)

English

Product Specifications Application Specification

English