		E A			16	Ω 7	14	α .	10	-7	0	G		a)	7	6	ຫ	4		ω	0	->	2 0]		١٩	DD	
AWING NO.		REMARKS	Tes:1 This tempareture includes a		SO2-EXPOSURE	H2S-EXPOSURE	(CORROSION).		TEMPERATURE CYCLING	SHOCK	VIBRATION	ALIGIMOH		WATING AND	CONTACT ENGAGEMENT AND SEPARATION FORCES	DAY CIRCUIT	LOW LEVEL CIRCUIT	DIELECTRIC WITHBTANDING	сонтаст	CONTACT RESISTANCE UNITCONTACT	INBULATION REBISTANCE	MARKING	DESIGN-MATERIAL-FINISH	Na L I		SPECIALTY	RATING POWER		`	APPLICABLE STANDARD	•	COUNT AEVISIONS
	CHECKED ORSIGNED ORAWN	12			ppm for	not have	sait water spray for	Must be less insertion and described in	Must have no parts for	5 2	Must have no demage, parts at Frequency amplitude mm, G	+ g	tion	Must be suitable value.	Must be suitable for the S value at applicable gauge.	Must have con	The Contact Resistance value at DC20mV le	Must withstand AC	voltage DC	The voltage of at DC 0./	Must be ov	Applicable	١١					CONTACT No.	CONTACT No. AC	Ρ.		SNO
	222				hours	hours	heavy	than the Std. extraction cycabove item No.	ر مر الم	amege, cycles	damage quency mm, G	× • • • • • • • • • • • • • • • • • • •	9 - 8 t 0		suitable for t applicable	DC duct iv	Resista DC20mV	3 d >	drop must	drop must		Std.		COND	g. Q.		ŀ	w	250	-		9 YB
100	Inviora.	loona	by l			. 007	3 6	tion tem			14.2	2 6	Ce	70° t	10 g	इ	1 e i		ist be	lat be	tandard	9 2 0			m		}	>	44	-		유 유
www	10 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Jonamo to	rise by heat's go		corrosion arte			+ 2 6	crack and looseness cycles.	crack and looseness at . G in direc	crack and looseness of snge — Hz, Total st hours for directic		must at	the Std.	the Std.	conductivity in alternate at DC	must be i	. V for	under	under	d value	8	ADC4	T I O N	CIF					ŀ		DATE
		155	enera		្តី	arter	after	after t the c	0086	0086	HZ.	20 20	2.0		gauge	nate	under	07.0	the Std.	the Std.	9 8 5	\alpha \alpha	9	ဖ	C				-	- 1		
(7.8.8.5 7.8.8.5	1.00	generation of				×	conc		ness	Total	5	משל		9		mA.		4		S	71502	7 5		\triangleright		19 19 19 19 19 19	E A	\ <u>\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\</u>	-		LOUNT
CODE NO.		-	of cor					on C	3	directions.	eness of t. Total directions.	after high humidity	et high humidity		812 c		Std.	minute.	vai ue	0 I CO	٠.	10-	- 1		OIL		OPERATING TEMPERATURE	EDANCE TOANCE	APPLICABLE			
]	connector w					MIL-STD-1344												MIL-STD-1344				TEST STANDARD	S		M PANGE	RANGE	CABLES		-	REVISIONS
- 1	- 24		nen e		-	ļ	ļ	44	ļ			<u> </u>		· 						344							ا ريا					S
L		o n	lect					1 1			1				1	1	1	ļ	1	ļ			1	Z			35	a				
	\mathcal{R}		when electricity		1	1	1	30		1	1		1			1		1		30		1	1	X X			ਹ	6		-		00
		SSUED			1	1	1	E E	1	1	ı	Σ	Σ	z	Z	1	Œ	1	E ·	Œ	Z a	1	1	STIND			+85'	}				BY CHKO
		УВ О	passes.					0												0		0	0	S QT			85°C (Notes1)		ľ			1 .
					1	1	T		1	1	. 1		1								-	0	0	 A			esi	H Z		.	. .	DATE

FICATION

SHEET

 $C\Gamma$

LC4

57-5-