

# Product data sheet

Specifications



## Metal industrial box plain door H200xW300xD80 IP66 IK10 RAL 7035

NSYSBM20308

### Main

|                          |                                       |
|--------------------------|---------------------------------------|
| Range                    | Spacial                               |
| Product name             | Spacial SBM                           |
| Device application       | Multi-purpose                         |
| Category                 | Industrial box                        |
| Device short name        | SBM                                   |
| Enclosure type           | Flat face box                         |
| Enclosure nominal height | 200 mm                                |
| Enclosure nominal width  | 300 mm                                |
| Enclosure nominal depth  | 80 mm                                 |
| Enclosure mounting       | Wall mounted                          |
| Device composition       | 4 cover screw<br>1 cover<br>1 body    |
| Body type                | Single piece body folded and welded   |
| Type of front cover      | Plain door                            |
| Cover fixing             | Half turn metal screw                 |
| Lock type                | Captive screw PZ2 outside sealed area |
| Removable parts          | Cover by captive screws               |

### Complementary

|                                     |                              |
|-------------------------------------|------------------------------|
| Material                            | Sheet steel                  |
| Surface finish                      | Polyester powder             |
| Colour                              | Grey (RAL 7035)              |
| Standards                           | IEC 62208                    |
| Product certifications              | LR<br>DNV-GL<br>UL<br>BV     |
| IP degree of protection             | IP66 conforming to IEC 60529 |
| IK degree of protection             | IK10 conforming to IEC 62262 |
| Ambient air temperature for storage | -35...60 °C                  |

|                       |             |
|-----------------------|-------------|
| Operating temperature | -35...80 °C |
| Net weight            | 2.128 kg    |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 9.5 cm   |
| Package 1 Width              | 21.5 cm  |
| Package 1 Length             | 31.5 cm  |
| Package 1 Weight             | 2.128 kg |
| Unit Type of Package 2       | P12      |
| Number of Units in Package 2 | 112      |
| Package 2 Height             | 105.0 cm |
| Package 2 Width              | 80.0 cm  |
| Package 2 Length             | 120.0 cm |
| Package 2 Weight             | 249.0 kg |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a>           |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope) |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

## Recommended replacement(s)