

## Power terminal block - AZK 35 - 0702997

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Power terminal block, Connection method Screw connection, Load current : 125 A, Cross section: 0.75 mm<sup>2</sup> - 35 mm<sup>2</sup>, Width: 12 mm, Color: aluminum


### Product description

Power terminal block, Connection method Screw connection, Load current : 125 A, Cross section: 0.75 mm<sup>2</sup> - 35 mm<sup>2</sup>, Width: 12 mm, Color: aluminum

### Why buy this product

- It is often necessary to branch flat copper busbars in switchgear
- This can be done easily with the branch terminal block because the terminal block can later be attached and firmly clamped anywhere on a copper rail (up to max. 5 mm thick)

### Key commercial data

|                                      |   |
|--------------------------------------|---|
| Packing unit                         | 1   |
| Minimum order quantity               | 10  |
| Catalog page                         | Page 501 (CL1-2011)   |
| GTIN                                 | <br>4 017918 003647 |
| Weight per piece (including packing) | 0.0 GRM   |
| Weight per Piece (excluding packing) | 41.91 GRM   |
| Country of origin                    | GERMANY   |

### Technical data

#### General

|       |          |
|-------|----------|
| Color | aluminum |
|-------|----------|

#### Dimensions

|        |       |
|--------|-------|
| Length | 40 mm |
| Width  | 12 mm |

#### Technical data

|                                |   |
|--------------------------------|---|
| Maximum load current           | 125 A (with 35 mm <sup>2</sup> conductor cross section) |
| Nominal current I <sub>N</sub> | 125 A   |

#### Connection data

|                                    |                      |
|------------------------------------|----------------------|
| Conductor cross section solid min. | 0.75 mm <sup>2</sup> |
| Conductor cross section solid max. | 35 mm <sup>2</sup>   |

# Power terminal block - AZK 35 - 0702997

## Technical data

### Connection data

|   |                      |
|---|----------------------|
| Conductor cross section stranded min.   | 0.75 mm <sup>2</sup> |
| Conductor cross section stranded max.   | 35 mm <sup>2</sup>   |
| Conductor cross section AWG/kcmil min.  | 18                   |
| Conductor cross section AWG/kcmil max   | 2                    |
| Conductor cross section stranded, with ferrule without plastic sleeve min.              | 0.75 mm <sup>2</sup> |
| Conductor cross section stranded, with ferrule without plastic sleeve max.              | 35 mm <sup>2</sup>   |
| Conductor cross section stranded, with ferrule with plastic sleeve min.                 | 0.75 mm <sup>2</sup> |
| Conductor cross section stranded, with ferrule with plastic sleeve max.                 | 35 mm <sup>2</sup>   |
| 2 conductors with same cross section, solid min.  | 0.75 mm <sup>2</sup> |
| 2 conductors with same cross section, solid max.  | 10 mm <sup>2</sup>   |
| 2 conductors with same cross section, stranded min.                                     | 0.75 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded max.                                     | 10 mm <sup>2</sup>   |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, min.   | 0.75 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, max.   | 10 mm <sup>2</sup>   |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | 0.75 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 10 mm <sup>2</sup>   |
| Connection method   | Screw connection     |
| Stripping length  | 15 mm                |
| Screw thread  | M6                   |
| Tightening torque, min  | 3.2 Nm               |
| Tightening torque max   | 3.7 Nm               |

## Classifications

### eClass

|            |          |
|------------|----------|
| eClass 4.0 | 27141131 |
| eClass 4.1 | 27141131 |
| eClass 5.0 | 27141131 |
| eClass 5.1 | 27141131 |
| eClass 6.0 | 27141120 |

### etim

|          |          |
|----------|----------|
| ETIM 2.0 | EC000897 |
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC000897 |

# Power terminal block - AZK 35 - 0702997

## Classifications

unspsc

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |

## Approvals

### Certificates

---

Certification

GOST / GOST

---

Certification EX

---

Certification submitted

---

### Approval details

GOST

GOST

## Accessories

### Accessories

#### Tools

Screwdriver - SZS 1,0X6,5 VDE - 1205079

Screwdriver, bladed, VDE insulated, size: 1.0 x 6.5 x 150 mm, 2-component grip, with non-slip grip

