


CHT06C152J3GAFT050

COG HT 260C, Ceramic, 1500 pF, 5%, 25 VDC, COG, SMD, MLCC, High Temperature, 260C, 0603



Click here for the 3D model.

Dimensions	
Chip Size	0603
L	1.6mm +/-0.15mm
W	0.8mm +/-0.15mm
Т	0.8mm +/-0.07mm
S	0.7mm MIN
В	0.35mm +/-0.15mm

Packaging Specifications		
Packaging	Cut Reel	
Packaging Quantity	50	

General Information		
Series	COG HT 260C	
Style	SMD Chip	
Description	SMD, MLCC, High Temperature, 260C	
Features	High Temperature, Low ESR	
RoHS	Yes	
Termination	Gold	
Marking	No	
AEC-Q200	No	
Component Weight	3.7 mg	
Miscellaneous	Gold (Au) 30 - 70 micro inches.	
Shelf Life	78 Weeks	
MSL	1	

Specifications	
Capacitance	1500 pF
Measurement Condition	1 kHz 1.0Vrms
Capacitance Tolerance	5%
Voltage DC	25 VDC
Dielectric Withstanding Voltage	62.5 VDC
Temperature Range	-55/+260°C
Temperature Coefficient	COG
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC)	30PPM/C,1kHz 1.0Vrms
Dissipation Factor	0.1% 1 kHz 1.0Vrms
Aging Rate	0% Loss/Decade Hour
Insulation Resistance	100 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.