# JLITE

## LED EQUIPMENT LIGHTS

**JAMESON**

### Versatile Lighting For A Variety Of Applications

Durable housings, sealed construction and easy-mount brackets make Jameson JLite ideal for a wide variety of general-purpose lighting applications:  Construction vehicles, utility trucks, forklifts, ATV's, golf carts, boats and more!

- IP65 – Protected against dust, dirt and low-pressure water jets
- Durable powder-coated die-cast aluminum housing
- Corrosion resistant stainless steel mounting bracket
- Impact resistant polycarbonate lens

- Various beam patterns
- 30,000 hours rated life
- CE and RoHS certifications
- One (1) year warranty

JL33C5W

500 Lumens

JL2C7S
JL2C7W

650 Lumens

JL11800-FL

1800 Lumens

JL16C28M
JL16C28W

2520 Lumens

JL13C48W

2700 Lumens

JL13C65S
JL13C65W

5460 Lumens

JL9C90S
JL9C90W

6750 Lumens

| | JL33C5W | JL2C7W | JL11800-FL | JL16C28W | JL13C48W | JL13C65S | JL13C65W | JL9C90S | JL9C90W |
|---|---|---|---|---|---|---|---|---|---|
| Effective Lumens | 500 | 650 | 1800 | 2520 | 2700 | 5460 | | 6750 | |
| Number of LEDs | 33 | 2 | 8 | 16 | 13 | 13 | | 9 | |
| Beam Patterns | Wide | Wide | Flood | Wide | Wide | Spot | Wide | Spot | Wide |
| Ingress Protection | IP65 | | | | | | | | |
| Power | 5 Watts | 7 Watts | 18 Watts | 28 Watts | 30 Watts | 65 Watts | | 90 Watts | |
| Current | 0.4 A @ 12 VDC 0.2 A @ 24 VDC | 0.6 A @ 12 VDC 0.3 A @ 24 VDC | 1.4A @ 12VDC 0.7A @ 24VDC | 2.3 A @ 12 VDC 1.2 A @ 24 VDC | 2.5 A @ 12 VDC 1.3 A @ 24 VDC | 5.4 A @ 12 VDC 2.7 A @ 24 VDC | | 6.3 A @ 12 VDC 3.2 A @ 24 VDC | |
| Voltage | 10-30VDC | | 12-24 VDC | 10-30VDC | | | | | |
| Operating Temp | -4°F to 122°F    (-20°C to 50°C) | | | | | | | | |
| Color Temp (CCT) | 6000K Cool White | | | | | | | | |
| Weight | 0.22 lbs (0.1 kg) | 0.25 lbs (0.1 kg) | 1.43 lbs (0.6 kg) | 0.71 lbs (0.3 kg) | 1.1 lbs (0.5 kg) | 2.69 lbs (1.2 kg) | | 6.39 lbs (2.9 kg) | |
| Dimensions | 3.7" x 3.0" x .91" | 3.7" x 2.4" x 1.8" | 5.6" x 4" x 2.3" | 5.5" x 4.3" x 1.9" | 5.7" x 4.9" x 2.8" | 6.5" x 5.6" x 3.7" | | 6.3" x 5.3" x 4.7" | |
| Termination | 6" Wire Lead with Deutsch Connector (Mating Connector Included) | | | | | | | | |



## JLITE WIRING HARNESSES

Sold Separately

| Wiring | |
|---|---|
| JLWH-DT1 | 14' Wiring Harness With On/Off Switch & One Deutsch Connector, Battery Ring Terminals |
| JLWH-DT2 | 14' Wiring Harness With On/Off Switch & Two Deutsch Connectors, Battery Ring Terminals |
| JLWH-DT1-CIG | 12' Wiring Harness, One Deutsch Connector & 12V Auto Plug Adapter, 10A Fuse |

Visit Our Website To See Our Full Line Of Lighting Products