## 24 INCHES LENGTH



Connector A 132245 SMA Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-316 Continuity/Hi-Pot Connector B 142233 SMB Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink

## Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Connector B	Connector A			Cable			Connector B		
90°	Part #:	132245		Part #:	RG-316		Part #:	142233	
135"	Description:	SMA R/A BHD JK 500	RG174 RG316 LMR100	Description: Dielectric:	RG-316 - ST ST	RG-316 - ST 0.102 ST	Description:	SMB R/A BHD JK R 500	G174 RG316 LMR100
180° 0°	Туре:	SMA		Shielding:	Braid		Туре:	SMB	
	Gender:	Jack		Diameter:	0.102		Gender:	Jack	
225* 1 315*	Body Type:	Right Angle		Impedance: 50 Ohm			Body Type:	Right Angle	
270"	Contact Type:	Solder Standard		Sheathing: Testing:	None	None	Contact Type:	Solder Standard	
6262	Polarity:				Continuity Hi-Pot	-Pot	Polarity:		
	Impedance:	50 Ohm		Length:	24 Inches		Impedance:	50 Ohm	
<b>A</b>	Mounting:	Bulkhead - Rear Mount		-			Mounting:	Bulkhead - Rear Mount	
	Body Material:	Brass					Body Material:	Brass	
	Body Finish:	Gold					Body Finish:	Gold	
	IP Rating: None						IP Rating:	None	
Connector A	Contact Material:	Material: Beryllium Copper					Contact Material:	Brass	
	Contact Finish:	Gold					Contact Finish:	Gold	
	Max. Freq.:	12.4 GHz					Max. Freq.:	4 GHz	
	Booting:	oting: SMA Jack Right Angle					Booting:	SMB Jack Right Angle 0°	
							Clocking:		
Amphenol FOR ANY PURPOSE DI INC. IT MAY NOT BE F			THIS DRAWING MAY CONTAIN PROPRIETARY INFORMATION A FOR ANY PURPOSE DETRIMENT INC. IT MAY NOT BE REPRODUC IN ANY FORM WITHOUT THE W	AND MUST NOT BE U FAL TO CUSTOM CAE CED OR TRANSCRIBE	BLE ED	Title: SMA-RA-JK/SMB-RA-JK G316 24I			UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY:
<b>CONTROLLED DOCUMENT - DO NOT COPY</b>			CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.			Part No: Q-2P03H0005024I			CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES



## **RoHS 2015/863 Compliance Statement**

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Complaint).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

Date: 10/3/2023

Part Number: Q-2P03H0005024I

Manufacturer: Amphenol Custom Cable

Description: SMA-RA-JK/SMB-RA-JK G316 24I

This information is valid as of the date indicated for the item (part number) listed.

**Director of Quality Assurance** 

Janice Frank