

ELECTRICAL CHARACTERISTICS: (ALL DATA APPLIES AT 23° C UNLESS OTHERWISE SPECIFIED)

COIL DATA:

NOMINAL VOLTAGE: 12 VDC
 OPERATE VOLTAGE: 7.2 VDC MAXIMUM
 RELEASE VOLTAGE: 1.2 VDC MINIMUM
 EQUIVALENT RESISTANCE: 79.5 OHMS ± 10%
 OPERATE TIME: 8 mSEC MAXIMUM EXCLUDING BOUNCE
 RELEASE TIME: 8 mSEC MAXIMUM EXCLUDING BOUNCE
 TEMPERATURE RANGE: STORAGE -40° C TO +155° C
 OPERATE -40° C TO +85° C
 OPERATE -40° C TO +125° C (APPLICATION DEPENDENT)

CONTACT DATA: (CONTACT DATA IS FORMATTED N.O./N.C.)

CONTACT ARRANGEMENT: 1 FORM C (SPDT)
 CONTACT MATERIAL: AgSnO2
 CONTACT MILLIVOLT DROP: 200 mV AT 40A ON N.O. CONTACTS (AFTER SWITCHING)
 250 mV AT 30A ON N.C. CONTACTS (AFTER SWITCHING)


MAXIMUM MAKE CURRENT: 120A/45A (LAMP) AT 16 VDC
 MAXIMUM BRAKE CURRENT: 60A/40A AT 16 VDC RESISTIVE
 MAXIMUM CONTINUOUS CURRENT: 60A/40A AT 23° C, 40A/30A AT 85° C
 INITIAL BREAKDOWN VOLTAGE: 500V RMS CONTACTS TO COIL

EXPECTED LIFE: 100,000 OPERATIONS, 40A, 14 VDC RESISITIVE ON NORMALLY OPEN CONTACT

MECHANICAL CHARACTERISTICS:

EXPECTED LIFE: 10 MILLION OPERATIONS, NO CONTACT LOAD, 20 OPERATIONS PER SECOND MAXIMUM

ENCLOSURE: EPOXY-SEALED



PROPRIETARY THE REPRODUCTION, TRANSMISSION OR USE OF THIS DOCUMENT OR IT'S CONTENTS IS NOT PERMITTED WITHOUT EXPRESSED WRITTEN AUTHORITY. OFFENDERS WILL BE LIABLE FOR ALL DAMAGES. ALL RIGHTS, INCLUDING RIGHTS CREATED BY REGISTERED PATENT(S) GRANTED FOR A UTILITY MODEL OR DESIGN, ARE RESERVED.			CHANGES TO THIS DRAWING MUST BE DONE ONLY IN CAD	PAPER SIZE A3	
APPLICABLE SPEC.:			FINISH		
		TOLERANCE UNLESS SPECIFIED OTHERWISE	DIMENSIONS IN MM	SCALE	WEIGHT
			MATERIAL		
			PART NAME		
			DATA SHEET V23134-A3052-X540		
			DWG NO.		SHT. 1 OF 1
A Initial Release	14NOV2016	KBieh			
REV. CHANGE ORDER	DATE	APP.			