



- NOTES**
1. MATERIAL: SOCKET PLUG POLYAMIDE(PA66), 40% MINERAL FILLED, UL94HB
TERMIANL: COPPER-ALLOY, 0.3T
OTHERS: SEE TABLE
 2. FINISH: SEE TABLE
 3. PRODUCT SPECIFICATION: PS-35340-001
 4. "F" DIMENSION:
1IEGE SPECIFICATION: 11.7mm
2KKS: 13.3mm
 5. MATES WITH 35512

GRAY	1	POLYAMIDE	SOCKET PLUG	355120200	35512-0200	⑥
12V 5W	1	-	BULB	-	-	⑤
RED	1	SILICON	INNER SEAL	359030011	35903-0011	④
DARK GRAY	1	RUBBER	O-RING	359030013	35903-0013	③
-	2	Cu-ALLOY	TERMINAL	350756100	35075-6100	②
GRAY	1	POLYAMIDE	STS HEADER	353410290	35341-0290	①
-	-	-	SOCKET ASSY	353410210	35341-0210	①
FINISH	Q'TY	MATERIAL	DECRPTION	MATERIAL NO	ENG NO	NO

CHANGED OF MATERIAL EIC NO: KOR2008-0070 DRW: NEEKIM 2007/10/04 CHK: BCYON 2007/10/04 APPR: YUNSIKIM 2007/10/02	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 2:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION			
		4 PLACES ± --- ± ---	3 PLACES ± --- ± ---	2 PLACES ± 0.2 ± ---	1 PLACE ± 0.2 ± ---	ANGULAR ± 1 °		DRAWN BY DATE YSOOKIM 1996/01/05		CHECKED BY DATE JKOH 1996/01/05	
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO. 353410210		DOCUMENT NO. SD-35341-001		MOLEX INCORPORATED		SHEET NO. 1 OF 1	
		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION									

