

Crimping tool for D-SUB Contacts



- Automatic lock guarantees quality crimp
- Unlocking option in the event of a incorrect operation
- With stop for exact positioning of the contacts



Technical specifications


Discription: Crimping tool for D-SUB Contacts

Type: Wire size Awg 28-20

Crimp profile 1: min. AWG 28 max. AWG 24

Crimp profile 2: min. AWG 22 max. AWG 20

COMMENT:
ALL RIGHTS ARE RESERVED BY US FOR THIS DRAWING. WITHOUT OUR PRIOR CONSENT,
IT MAY NEITHER BE DUPLICATED NOR MADE AVAILABLE TO A THIRD PARTY,
AND IT ALSO MAY NOT BE IMPROPERLY USED BY THE RECEIVER, OR A THIRD PARTY.

SYMBOLS										THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION									
DIMENSION UNITS		SCALE		MEASUREMENTS WITHOUT TOLERANCE ACC. TO ISO 2768-m						molex									
mm		1:1		CURRENT REVISION															
REV.		CH.-NO.		DRWN: DRAWN BY		mteubel		07-12-2021		PRODUCT CUSTOMER DRAWING									
1				APPR: APPR BY		fvetter		10-12-2021											
2				INITIAL REVISION						MATERIAL NUMBER									
1				DRWN: DRAWN BY		mteubel		07-12-2021		1731120337									
1				APPR: APPR BY		fvetter		10-12-2021		REVISION									
1				REPLACEMENT FOR:		THIRD ANGLE PROJECTION		DRAWING		DOCUMENT NUMBER				CUSTOMER		SHEET NUMBER			
1								A4-SIZE		F1089_D				GENERAL MARKET		1 OF 1			