

## 208/240V Single Phase Whip in 30 ft. (9.14 m) length with L6-30R for Breakered 3-Phase Distribution Cabinets

MODEL NUMBER: **SUWL630C-30**



### Highlights

- 208/240V single phase whip distribution cabinet accessory
- 30-ft. (9.14 m) length with 3-ft. (0.91 m) removed outer jacket
- 3 conductor 10AWG stranded wire
- L6-30R outlet (208/240V 30A)

### Description

208/240V single phase whip with L6-30R outlet distributes power from 3 phase distribution cabinet to critical equipment racks. 30-ft. (9.14 m) insulated and 3-ft. (0.91 m) of removed outer jacket cabling supports hardwire connection to SUBB230 circuit breaker in SUDC208V series 3 phase distribution racks. L6-30R outlet is compatible with 208/240V loads and Power Distribution Units (PDUs) supporting a L6-30P plug-in connection.

### Features

- 208/240V single phase whip with L6-30R outlet
- Distributes power from 3 phase distribution cabinet to critical equipment racks
- 30-ft. (9.14 m) insulated and 3-ft. (0.91 m) of removed outer jacket cabling supports hardwire connection to SUBB230 circuit breaker in SUDC208V series 3 phase distribution racks
- L6-30R outlet is compatible with 208/240V loads and Power Distribution Units (PDUs) supporting a L6-30P plug-in connection

## Specifications

OVERVIEW	
UPC Code	037332156228
Product Type	Single-Phase Whip Cable
Accessory Type	Single-Phase Whip Cable
Accessory Class	PDU Accessories
INPUT	
Input Connection Type	Hardwire (3 wire - L, N, G)

OUTPUT	
PDU Recommendation Notes	Compatible with all PDU brands fitted with a L6-30P (30A 208/240V) input plug, including Tripp Lite & <a href="//www.tripplite.com/4.8-5.8kW-Single-Phase-Basic-PDU-200-240V-Outlets-16-C13-4-C19-L6-30P-15ft-Cord-1U-Rack-Mount-PDU1230">PDU1230</a> & <a href="//www.tripplite.com/5-5.8kW-Single-Phase-Basic-PDU-208-240V-Outlets-6-C19-32-C13-L6-30P-10ft-Cord-0U-Vertical-PDUV30HV">PDUV30HV</a> & <a href="//www.tripplite.com/5.8kW-Single-Phase-Metered-PDU-208-240V-Outlets-16-C13-2-C19-L6-30P-12ft-Cord-2U-Rack-Mount-TAA-PDUMH30HV">PDUMH30HV</a> & <a href="//www.tripplite.com/5-5.8kW-Single-Phase-Metered-PDU-208-240V-Outlets-6-C19-24-C13-L6-30P-10ft-Cord-0U-Vertical-PDUMV30HV">PDUMV30HV</a> & <a href="//www.tripplite.com/server-rack-pdu-monitored-2u-120v-10-ft-cord-taa-PDUMNH30">PDUMNH30</a> & <a href="//www.tripplite.com/5.8kW-Single-Phase-Switched-PDU-208-240V-Outlets-8-C13-6-C19-L6-30P-15ft-Cord-2U-Rack-Mount-PDUMH30HV19NET">PDUMH30HV19NET</a> & <a href="//www.tripplite.com/5.8kW-Single-Phase-Switched-PDU-208-240V-Outlets-16-C13-L6-30P-Input-12ft-Cord-2U-Rack-Mount-TAA-PDUMH30HVNET">PDUMH30HVNET</a> & <a href="#">PDU1230</a> ; and <a href="#">PDUV30HV</a> ; and <a href="#">PDUMV30HV</a> ; and <a href="#">PDUMNH30</a> ; and <a href="#">PDUMH30HV19NET</a> ; and <a href="#">PDUMH30HVNET</a>
Output Receptacles	(1) L6-30R
PHYSICAL	
Color	Black
Cable Length (ft.)	30
Cable Length (m)	9.15
Shipping Dimensions (hwd / in.)	6.30 x 12.00 x 12.00
Shipping Dimensions (hwd / cm)	16.00 x 30.48 x 30.48
Shipping Weight (lbs.)	11.20
Shipping Weight (kg)	5.08
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	1-year limited warranty