
SPECIFICATION CONTROL DRAWING



		GA = WIRE GAUGE (AWG)								-	
Product Revision		Product Dimensions									
Product Name		øΑ	øB	øС	øD	øΕ	øF	L1	L2	K	AWG
		min	min	min	min	min	min	max	max	min	
D-181-2220-90/9	F										20
D-181-2222-90/9	F	4.50	4.00	3.45	2.90	3.00	1.10	17.00	22.7	150	22
D-181-2224-90/9	F	(0.180)	(0.160)	(0.135)	(0.115)	(0.120)	(0.045)	(0.670)	(0.895)	(5.900)	24
D-181-2226-90/9	F										26

MATERIALS

- 1. INSULATION SLEEVE: Heat-shrinkable, transparent blue, radiation cross-linked modified polyvinylidene fluoride.
- 2. SOLDER PREFORM WITH FLUX:

TYPE Sn63 per ANSI-J-STD-006. SOLDER:


FLUX: TYPE ROL1 per ANSI-J-STD-004.

- 3. MELTABLE RINGS: Thermally stabilized thermoplastic. Color: gray.
- 4. GROUND LEAD: Raychem 55A0111-GA-9 in accordance with MIL-W-22759/32, AWG GA (see table), stranded tin plated.
- 5. GROUND LEAD: Raychem 55A0111-GA-90 in accordance with MIL-W-22759/32, AWG GA (see table), stranded tin plated. Color: white with black stripe.

APPLICATION

- 1. These parts are designed to provide an environment protected coaxial termination on cables, rated for 125°C minimum, meeting the dimensional criteria listed, having a tin or silverplated copper shields.
- 2. Temperature range: -55°C to +150°C. Install using Raychem-approved convection or infrared heating tools in accordance with Raychem process standard RCPS-200-36.

For best results, prepare the cable as shown:



SolderSleeve is a trademark of Tyco Electronics Corporation.

tyco Electronics	300 Constit			s Corporation n Drive, a. 94025, U.S.A.	Raychem	TITLE: COAXIAL SOLDERSLEEVE DEVICE WITH PRE-INSTALLED LEAD				
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. INCHES DIMENSIONS ARE BETWEEN BRACKETS.						DOCUMENT NO.: D-181-22GA-90/9				
TOLERANCES: 0.00 N/A 0.0 N/A 0 N/A	ROU	ANGLES: N/A ROUGHNESS IN MICRON		drawing at any time	es the right to amend Users should of the product for their	DATE: Jun. 15, 1998		DOC ISSUE:		
DRAWN BY: M. FOROND	DRAWN BY: CAGE M. FORONDA (REPLACES: D18122XX	DCR NUMBER: D981012	PROD. REV.: SEE TABLE	SCALE: None	SIZE:	SHEET: 1 of 1	