



MATERIAL NO	ENGR. NUMBER	PULSE-START
1301100038	8575-MH	NO
1301100050	8575-MH-PS	YES



NOTES:

- 400W METAL HALIDE BULB
- PRODUCT TO BE SUPPLIED WITH A METAL HALIDE LAMP THAT INCORPORATES A QUARTZ SHROUD AND IS RATED O-TYPE TO COMPLY WITH ANSI STANDARD C78.387 FOR CONTAINMENT TEST AND USE IN OPEN LUMINARIES.
- SPRING-LOADED HOOK AND MOLDED CORDSET.
- OVERALL LENGTH WITH WIRE GUARD: 22.9 IN. (582MM).
- PULSE-START TECHNOLOGY IS REQUIRED IN THE U.S. (8575-MH FOR USE IN CANADA ONLY).
- PRODUCT IS WIRED FOR 120V. QUAD-TAP BALLAST PROVIDES FOR OPTIONAL VOLTAGES OF 208V, 240V, 277V.

RELEASE SALES DRAWING EC NO: IPG2013-0873 DRWN: HRUIZ01 2012/12/10 CH'KD: HKNEELAN APPR: DTITUS 2013/01/30	QUALITY SYMBOL	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE IN/MM		SCALE NTS	DESIGN UNITS INCH	THIRD ANGLE PROJECTION	
	▽=0	4 PLACES	mm ±---	INCH ±---	DRAWN BY HRUIZ01	DATE 2012/12/10	TITLE 400W METAL HALIDE HIGH BAY TEMPORARY LIGHTING FIXTURE		
	∇=0	3 PLACES	±---	±.005	CHECKED BY HKNEELAN	DATE 2012/12/28			
		2 PLACES	±0.13	±.010	APPROVED BY DTITUS	DATE 2013/01/30	MOLEX INCORPORATED		
	1 PLACE	±0.25	±.020	ANGULAR ±1/2°		MATERIAL NO. SEE CHART	DOCUMENT NO. SD-130110-002	SHEET NO. 1 OF 1	
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					