



Scan the QR code and visit the product page



|                          |   |                             |             |
|--------------------------|---|-----------------------------|-------------|
| Code                     | <b>TK.LB.D0030.AEC</b>  | Safety level                | Danger      |
| Dimensions (H x L)       | 69 mm x 140 mm (2,7" x 5,5")  | Version                     | Standard    |
| Material                 | PVC base with adhesive liner and protective layer   | Temperatures <sup>(1)</sup> | -40°C/+95°C |
| Applications             | Machinery and control panels. Indoor and outdoor locations  |                             |             |
| Languages <sup>(2)</sup> | Inglese   |                             |             |
| Message <sup>(3)</sup>   | EN: Moving parts can crush and cut. Keep hands clear. Lockout/tagout before servicing.<br>IT: Le parti in movimento possono schiacciare e tagliare. Tieni le mani a distanza. Blocca e identifica prima della manutenzione. |                             |             |
| Certifications           | c(UL)us Recognized - File#MH60136 (PDGQ2, PGDQ8)  |                             |             |
| Standards of use         | ANSI Z535, OSHA Art. 1910.145, NFPA 70 (NEC), NFPA 79, UL 508A, CSA C22.1 (CECode), CSA C22.2 No.286  |                             |             |
| Standards Construction   | ANSI Z535, UL 969, CSA C22.2 No.0.15, ISO 3864, RoHS  |                             |             |
| Standard packaging       | 12 pz/pcs   |                             |             |

(1) For indoor and outdoor exposure with high humidity or with occasional exposure to water. The minimum application temperature is +0°C. UL certification is for maximum working temperatures of +60°C.

(2) Other languages may have different sizes and available upon request.

(3) The message and the image are shown in English language only.