

**Data sheet | Item number: 254-200**

End plate; 1 mm thick; snap-fit type; dark gray

[www.wago.com/254-200](http://www.wago.com/254-200)



Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



## Data

### Physical data

Width	1 mm / 0.039 inches
Height	15.7 mm / 0.618 inches
Depth	13.5 mm / 0.531 inches

### Mechanical Data

Mounting type	snap-on type
---------------	--------------

### Material Data

Note (material data)	Information on material specifications can be found here
----------------------	--

Color	dark gray
Material group	I
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.005 MJ
Weight	0.2 g

### Commercial data

Product Group	4 (Printed Circuit Connectors)
eCl@ss 10.0	27-44-04-92
eCl@ss 9.0	27-44-04-92
ETIM 8.0	EC000886
ETIM 7.0	EC000886
PU (SPU)	2000 (100) pcs
Packaging type	box
Country of origin	CH
GTIN	4017332268806
Customs tariff number	85389099990

### Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Subject to changes. Please also observe the further product documentation!



## Approvals / Certificates

### Approvals for marine applications

Logo	Approval	Additional Approval Text	Certificate name
	<b>BV</b> Bureau Veritas S.A.	IEC 60998	11915/D0 BV

## Required accessories

### End plate

PCB terminal block		
<b>Item no.: 254-802</b>	Stackable 2-conductor PCB terminal block; 0.75 mm <sup>2</sup> ; Pin spacing 5/5.08 mm; 1-pole; PUSH WIRE®; 0,75 mm <sup>2</sup> ; dark gray	<a href="http://www.wago.com/254-802">www.wago.com/254-802</a>
<b>Item no.: 254-822</b>	Stackable 2-conductor PCB terminal block; 0.75 mm <sup>2</sup> ; Pin spacing 10/10.16 mm; 1-pole; PUSH WIRE®; 0,75 mm <sup>2</sup> ; dark gray	<a href="http://www.wago.com/254-822">www.wago.com/254-822</a>
<b>Item no.: 254-812</b>	Stackable 2-conductor PCB terminal block; 0.75 mm <sup>2</sup> ; Pin spacing 7.5/7.62 mm; 1-pole; PUSH WIRE®; 0,75 mm <sup>2</sup> ; dark gray	<a href="http://www.wago.com/254-812">www.wago.com/254-812</a>
<b>Item no.: 254-843</b>	Stackable PCB terminal block; 2.5 mm <sup>2</sup> ; Pin spacing 5/5.08 mm; 1-pole; PUSH WIRE®; 2,50 mm <sup>2</sup> ; light gray	<a href="http://www.wago.com/254-843">www.wago.com/254-843</a>
<b>Item no.: 254-844</b>	Stackable PCB terminal block; 2.5 mm <sup>2</sup> ; Pin spacing 5/5.08 mm; 1-pole; PUSH WIRE®; 2,50 mm <sup>2</sup> ; blue	<a href="http://www.wago.com/254-844">www.wago.com/254-844</a>
<b>Item no.: 254-842</b>	Stackable PCB terminal block; 2.5 mm <sup>2</sup> ; Pin spacing 5/5.08 mm; 1-pole; PUSH WIRE®; 2,50 mm <sup>2</sup> ; dark gray	<a href="http://www.wago.com/254-842">www.wago.com/254-842</a>
<b>Item no.: 254-846</b>	Stackable PCB terminal block; 2.5 mm <sup>2</sup> ; Pin spacing 5/5.08 mm; 1-pole; PUSH WIRE®; 2,50 mm <sup>2</sup> ; orange	<a href="http://www.wago.com/254-846">www.wago.com/254-846</a>
<b>Item no.: 254-847</b>	Stackable PCB terminal block; 2.5 mm <sup>2</sup> ; Pin spacing 5/5.08 mm; 1-pole; PUSH WIRE®; 2,50 mm <sup>2</sup> ; light green	<a href="http://www.wago.com/254-847">www.wago.com/254-847</a>
<b>Item no.: 254-852</b>	Stackable PCB terminal block; 2.5 mm <sup>2</sup> ; Pin spacing 7.5/7.62 mm; 1-pole; PUSH WIRE®; 2,50 mm <sup>2</sup> ; dark gray	<a href="http://www.wago.com/254-852">www.wago.com/254-852</a>
<b>Item no.: 254-854</b>	Stackable PCB terminal block; 2.5 mm <sup>2</sup> ; Pin spacing 7.5/7.62 mm; 1-pole; suitable for Ex-i applications; PUSH WIRE®; 2,50 mm <sup>2</sup> ; blue	<a href="http://www.wago.com/254-854">www.wago.com/254-854</a>
<b>Item no.: 254-853</b>	Stackable PCB terminal block; 2.5 mm <sup>2</sup> ; Pin spacing 7.5/7.62 mm; 1-pole; PUSH WIRE®; 2,50 mm <sup>2</sup> ; light gray	<a href="http://www.wago.com/254-853">www.wago.com/254-853</a>
<b>Item no.: 254-856</b>	Stackable PCB terminal block; 2.5 mm <sup>2</sup> ; Pin spacing 7.5/7.62 mm; 1-pole; PUSH WIRE®; 2,50 mm <sup>2</sup> ;	<a href="http://www.wago.com/254-856">www.wago.com/254-856</a>

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



orange

**Item no.: 254-857**

Stackable PCB terminal block; 2.5 mm<sup>2</sup>; Pin spacing 7.5/7.62 mm; 1-pole; PUSH WIRE®; 2,50 mm<sup>2</sup>; light green [www.wago.com/254-857](http://www.wago.com/254-857)

**Item no.: 254-863**

Stackable PCB terminal block; 2.5 mm<sup>2</sup>; Pin spacing 10/10.16 mm; 1-pole; PUSH WIRE®; 2,50 mm<sup>2</sup>; light gray [www.wago.com/254-863](http://www.wago.com/254-863)

**Item no.: 254-864**

Stackable PCB terminal block; 2.5 mm<sup>2</sup>; Pin spacing 10/10.16 mm; 1-pole; suitable for Ex-i applications; PUSH WIRE®; 2,50 mm<sup>2</sup>; blue [www.wago.com/254-864](http://www.wago.com/254-864)

**Item no.: 254-866**

Stackable PCB terminal block; 2.5 mm<sup>2</sup>; Pin spacing 10/10.16 mm; 1-pole; PUSH WIRE®; 2,50 mm<sup>2</sup>; orange [www.wago.com/254-866](http://www.wago.com/254-866)

**Item no.: 254-867**

Stackable PCB terminal block; 2.5 mm<sup>2</sup>; Pin spacing 10/10.16 mm; 1-pole; PUSH WIRE®; 2,50 mm<sup>2</sup>; light green [www.wago.com/254-867](http://www.wago.com/254-867)

**Item no.: 254-862**

Stackable PCB terminal block; 2.5 mm<sup>2</sup>; Pin spacing 10/10.16 mm; 1-pole; PUSH WIRE®; 2,50 mm<sup>2</sup>; dark gray [www.wago.com/254-862](http://www.wago.com/254-862)

**Item no.: 254-451**

Stackable PCB terminal block; 2.5 mm<sup>2</sup>; Pin spacing 5/5.08 mm; 1-pole; PUSH WIRE®; 2,50 mm<sup>2</sup>; gray [www.wago.com/254-451](http://www.wago.com/254-451)

**Item no.: 254-551**

Stackable PCB terminal block; 2.5 mm<sup>2</sup>; Pin spacing 7.5/7.62 mm; 1-pole; PUSH WIRE®; 2,50 mm<sup>2</sup>; gray [www.wago.com/254-551](http://www.wago.com/254-551)

**Item no.: 254-651**

Stackable PCB terminal block; 2.5 mm<sup>2</sup>; Pin spacing 10/10.16 mm; 1-pole; PUSH WIRE®; 2,50 mm<sup>2</sup>; gray [www.wago.com/254-651](http://www.wago.com/254-651)

**Downloads**

**Documentation**

**Additional Information**

2019 年4月3日

pdf  
2.0 MB

Download

**CAD/CAE-Data**

**CAD data**

2D/3D Models 254-200

URL

Download

**CAE data**

EPLAN Data Portal 254-200

URL

Download

ZUKEN Portal 254-200

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.



[URL](#)

[Download](#)

---

## Environmental Product Compliance

### Compliance Search

Environmental Product Compliance 254-200

[URL](#)

[Download](#)

End plate; 1 mm thick; snap-fit type; dark gray

---

## Installation Notes

Subject to changes. Please also observe the further product documentation!

---

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.