

Readability **0.5 kg – 1.1 lb**



► **Features**

- RS232 interface.
- Internal rechargeable battery.
- Diamond plate surface for added grip.
- 10m / 32' indicator cable
- High contrast LED display
- Auto shut-off
- Robust construction for demanding use
- Industrial rubber feet

► **Standard Functions**

- Weighing
- Parts counting
- Dynamic weighing
- Checkweighing
- Hold function

► **Accessories Included**

- 3 AA batteries
- Display Mount

| TECHNICAL DATA | | |
|-----------------------|--|-------------------|
| Model | VE-PS2000 | VE-PS3000 |
| Capacity | 2000 kg / 4400 lb | 3000 kg / 6600 lb |
| Readability | 0.5 kg/1.1 lb | 0.5 kg/1.1 lb |
| Repeatability | ±0.5 kg/1.1 lb | ±0.5 kg/1.1 lb |
| Linearity | ±1 kg/2.2 lb | ±1 kg/2.2 lb |
| Loadcells | 4 | |
| Cable length | 10m / 32' | |
| Weighing Units | kg, lb | |
| Calibration | External | |
| Pan Size | 1200 x 1200 mm / 47.2" x 47.2" | |
| Stabilization Time | 2 seconds | |
| Interface | RS232 | |
| Display | LCD, digit height 25mm / 1" | |
| Housing | Mild steel base | |
| Operating Environment | -10° to 40°C / 14° to 104°F | |
| Overall Dimensions | 1200 x 1200 x 110mm / 47.2" x 47.2" x 4.3" | |
| Power Supply | 110/240V, 50/60 Hz AC Adapter and rechargeable battery | |
| Net Weight | 175lb / 79kg | |
| Warranty | 1 year | |