



ELECTRICAL SPECIFICATIONS :

- Frequency range : 758 to 803 MHz
- Input power : 130 W
- Input power, peak : 1300 W
- Reflected power : 80 W
- Isolation (within frequency range, port 2 to 1) : 22 dB Min
- Return Loss (Measured at port 1 and port 2) : 23 dB Min (0°C-115°C)
(Measured at port 1 and port 2) : 20 dB Min (-40°C-0°C)
- Insertion Loss (within frequency range, port 1 to 2) : 0.25 dB Max
- Intermodulation distortion, IM3(2 x 50 W) : -65 dBc Max
IM5(2 x 50 W) : -79 dBc Max
- Harmonics: 2 x f(100W CW) : 0dBm Max
3-4 x f (100W CW) : -10 dBm Max
5 x f (100W CW) : -35dBm Max
6-7 x f (100W CW) : -25 dBm Max
- Operating temperature range: -40°C to +115°C
- Storage temperature range : -40°C to +115°C
- Direction : CW

BODY: STEEL, SILVER PLATED
RIGID PINS: COPPER, SILVER PLATED
NOTES:

1. STANDARD INPUT/OUTPUT IMPEDANCE 50 Ohm.
2. LEAD FREE, NO Nd MATERIAL, BeO FREE.
3. THE DIMENSION OF THE DATA MATRIX IS 7.6MM*7.6MM, INFORMATION INCLUDED WORK ORDER NUMBER-SERIAL NUMBER-MATERIAL NUMBER
4. THIS PART COMPLIES WITH ALL ROHS REQUIREMENTS

ENG PART#: 801-075-080-WB040

FUNCTIONAL SYMBOLS F=0 E=0 P=0	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC: RELEASE TO PROD		molex
	DIMENSION UNITS MM	SCALE 1:1	EC NO: 696580		
	GENERAL TOLERANCES (UNLESS SPECIFIED)		DRWN: SREN05	2022/02/21	
			CHK'D: JLI252	2022/02/23	
DIVISIONAL SYMBOLS			APPR: HWANG186	2022/03/01	RESTRICTED PRODUCT CUSTOMER DRAWING
			INITIAL REVISION:		DOCUMENT NUMBER
			DRWN: SREN05	2021/12/08	735912095
			APPR: HWANG186	2022/03/01	PSD 000 A
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING A3-SIZE	SERIES 73591	MATERIAL NUMBER 0735912095
			CUSTOMER CUSTOM PART		SHEET NUMBER 1 OF 1